



WATER-BASED DITHIOLENE INFRARED INKJET INKS

Field of the Invention

The present application relates to water-based infrared inkjet inks and dithiolene dyes suitable for
5 formulating such inks. It has been developed primarily to allow high-speed, high-throughput printing of dithiolene IR inks.

Co-pending Applications

Various methods, systems and apparatus relating to the present invention are disclosed in the following
10 co-pending applications filed by the applicant or assignee of the present invention simultaneously with the present application:

	<u>10/815621</u>	<u>10/815612</u>	<u>10/815630</u>	<u>10/815637</u>	<u>10/815638</u>	<u>10/815640</u>
	<u>10/815642</u>	<u>7097094</u>	<u>10/815644</u>	<u>10/815618</u>	<u>10/815639</u>	<u>10/815635</u>
	<u>10/815647</u>	<u>10/815634</u>	<u>10/815632</u>	<u>7131596</u>	<u>7128265</u>	<u>10/815641</u>
	<u>10/815645</u>	<u>10/815646</u>	<u>10/815617</u>	<u>10/815620</u>	<u>10/815615</u>	<u>10/815613</u>
	<u>10/815633</u>	<u>10/815619</u>	<u>10/815616</u>	<u>10/815614</u>	<u>10/815636</u>	<u>7128270</u>
	<u>10/815609</u>	<u>10/815627</u>	<u>10/815626</u>	<u>10/815610</u>	<u>10/815611</u>	<u>7097106</u>
	<u>7070110</u>	<u>10/815629</u>	<u>10/815624</u>	<u>10/815628</u>		

15 ~~10/815,621, 10/815,612, 10/815,630, 10/815,637, 10/815,638, 10/815,640,~~
~~10/815,642, 10/815,643, 10/815,644, 10/815,618, 10/815,639, 10/815,609,~~
~~10/815,627, 10/815,626, 10/815,610, 10/815,611, 10/815,623, 10/815,622,~~
~~10/815,629, 10/815,647, 10/815,634, 10/815,362, 10/815631, 10/815,648,~~
~~10/815,641, 10/815,645, 10/815,646, 10/815,617, 10/815,620, 10/815,615,~~
~~10/815,613, 10/815,633, 10/815,619, 10/815,616, 10/815,614, 10/815,624,~~
~~10/815,628, 10/815,636, 10/815,649, 10/815,635.~~

20 The disclosures of these co-pending applications are incorporated herein by cross-reference.

Background of the Invention

IR absorbing dyes have numerous applications, such as optical recording systems, thermal writing displays, laser filters, infrared photography, medical applications and printing. Typically, it is desirable for the dyes used in these applications to have strong absorption in the near-IR at the emission wavelengths of
25 semiconductor lasers (e.g. between about 700 and 2000 nm, preferably between about 700 and 1000 nm). In optical recording technology, for example, gallium aluminium arsenide (GaAlAs) and indium phosphide (InP) diode lasers are widely used as light sources.

Another important application of IR dyes is in inks, such as printing inks. The storage and retrieval of digital information in printed form is particularly important. A familiar example of this technology is the use of printed, scannable bar codes. Bar codes are typically printed onto tags or labels associated with a particular product and contain information about the product, such as its identity, price *etc.* Bar codes are usually printed in lines of visible black ink, and detected using visible light from a scanner. The scanner typically comprises an LED or laser (*e.g.* a HeNe laser, which emits light at 633 nm) light source and a photocell for detecting reflected light. Black dyes suitable for use in barcode inks are described in, for example, WO03/074613.

However, in other applications of this technology (*e.g.* security tagging) it is desirable to have a barcode, or other intelligible marking, printed with an ink that is invisible to the unaided eye, but which can be detected under UV or IR light.

An especially important application of detectable invisible ink is in automatic identification systems, and especially “~~netpage~~NETPAGE” and “Hyperlabel™” systems. ~~Netpage~~NETPAGE systems are described in the following patent applications, all of which are incorporated herein by reference.

<u>10/409876</u>	<u>10/409848</u>	<u>10/409845</u>	<u>09/575197</u>	<u>7079712</u>	<u>09/575123</u>
<u>6825945</u>	<u>09/575165</u>	<u>6813039</u>	<u>09/693415</u>	<u>6987506</u>	<u>6824044</u>
<u>6980318</u>	<u>6816274</u>	<u>7102772</u>	<u>09/575186</u>	<u>6681045</u>	<u>6678499</u>
<u>6679420</u>	<u>6963845</u>	<u>6976220</u>	<u>6728000</u>	<u>7110126</u>	<u>09/575145</u>
<u>6976035</u>	<u>6813558</u>	<u>6766942</u>	<u>6965454</u>	<u>6995859</u>	<u>7088459</u>
<u>6720985</u>	<u>09/609303</u>	<u>6922779</u>	<u>6978019</u>	<u>6847883</u>	<u>7131058</u>
<u>09/721895</u>	<u>09/607843</u>	<u>09/693690</u>	<u>6959298</u>	<u>6973450</u>	<u>09/609553</u>
<u>6965882</u>	<u>09/608022</u>	<u>09/575181</u>	<u>09/722174</u>	<u>09/721896</u>	<u>10/291522</u>
<u>6718061</u>	<u>10/291523</u>	<u>10/291471</u>	<u>7012710</u>	<u>6825956</u>	<u>10/291481</u>
<u>10/291509</u>	<u>10/291825</u>	<u>10/291519</u>	<u>7031010</u>	<u>6972864</u>	<u>6862105</u>
<u>7009738</u>	<u>6989911</u>	<u>6982807</u>	<u>10/291576</u>	<u>6829387</u>	<u>6714678</u>
<u>6644545</u>	<u>6609653</u>	<u>6651879</u>	<u>10/291555</u>	<u>10/291510</u>	<u>10/291592</u>
<u>10/291542</u>	<u>7044363</u>	<u>7004390</u>	<u>6867880</u>	<u>7034953</u>	<u>6987581</u>
<u>10/291556</u>	<u>10/291821</u>	<u>10/291525</u>	<u>10/291586</u>	<u>10/291822</u>	<u>10/291524</u>
<u>10/291553</u>	<u>6850931</u>	<u>6865570</u>	<u>6847961</u>	<u>10/685523</u>	<u>10/685583</u>
<u>10/685455</u>	<u>10/685584</u>	<u>10/757600</u>	<u>10/804034</u>	<u>10/793933</u>	<u>7068382</u>
<u>7007851</u>	<u>6957921</u>	<u>6457883</u>	<u>10/743671</u>	<u>7094910</u>	<u>7091344</u>
<u>7122685</u>	<u>7038066</u>	<u>7099019</u>	<u>7062651</u>	<u>6789194</u>	<u>6789191</u>
<u>6644642</u>	<u>6502614</u>	<u>6622999</u>	<u>6669385</u>	<u>6827116</u>	<u>6549935</u>

	<u>6987573</u>	<u>6727996</u>	<u>6591884</u>	<u>6439706</u>	<u>6760119</u>	<u>09/575198</u>
	<u>7064851</u>	<u>6826547</u>	<u>6290349</u>	<u>6428155</u>	<u>6785016</u>	<u>6831682</u>
	<u>6741871</u>	<u>6927871</u>	<u>6980306</u>	<u>6965439</u>	<u>6840606</u>	<u>7036918</u>
	<u>6977746</u>	<u>6970264</u>	<u>7068389</u>	<u>7093991</u>	<u>10/659026</u>	<u>6982798</u>
	<u>6870966</u>	<u>6822639</u>	<u>6474888</u>	<u>6627870</u>	<u>6724374</u>	<u>6788982</u>
	<u>09/722141</u>	<u>6788293</u>	<u>6946672</u>	<u>6737591</u>	<u>7091960</u>	<u>09/693514</u>
	<u>6792165</u>	<u>7105753</u>	<u>6795593</u>	<u>6980704</u>	<u>6768821</u>	<u>7132612</u>
	<u>7041916</u>	<u>6797895</u>	<u>7015901</u>	<u>10/782894</u>	<u>10/782895</u>	<u>10/778056</u>
	<u>10/778058</u>	<u>10/778060</u>	<u>10/778059</u>	<u>10/778063</u>	<u>10/778062</u>	<u>10/778061</u>
	<u>10/778057</u>	<u>7055739</u>	<u>09/575129</u>	<u>6830196</u>	<u>6832717</u>	<u>09/721862</u>
	<u>7082562</u>	<u>6843420</u>	<u>10/291718</u>	<u>6789731</u>	<u>7057608</u>	<u>6766944</u>
	<u>6766945</u>	<u>10/291715</u>	<u>10/291559</u>	<u>10/291660</u>	<u>10/409864</u>	<u>7108192</u>
	<u>7111791</u>	<u>10/786631</u>	<u>10/683151</u>	<u>10/683040</u>	<u>10/778090</u>	<u>6957768</u>
	<u>09/575162</u>	<u>09/575172</u>	<u>09/575170</u>	<u>7106888</u>	<u>7123239</u>	<u>6982701</u>
	<u>6982703</u>	<u>10/291538</u>	<u>6786397</u>	<u>6947027</u>	<u>6975299</u>	<u>10/291714</u>
	<u>7048178</u>	<u>7118025</u>	<u>6839053</u>	<u>7015900</u>	<u>7010147</u>	<u>7133557</u>
	<u>6914593</u>	<u>10/291546</u>	<u>6454482</u>	<u>6808330</u>	<u>6527365</u>	<u>6474773</u>
	<u>6550997</u>	<u>7093923</u>	<u>6957923</u>	<u>7131724</u>		

	10/409,876	10/409,848	10/409,845	09/575,197	09/575,195
	09/575,159	09/575,132	09/575,123	09/575,148	09/575,130
	09/575,165	09/575,153	09/693,415	09/575,118	09/609,139
5	09/608,970	09/575,116	09/575,144	09/575,139	09/575,186
	09/575,185	09/609,039	09/663,579	09/663,599	09/607,852
	09/575,191	09/693,219	09/575,145	09/607,656	09/693,280
	09/609,132	09/693,515	09/663,701	09/575,192	09/663,640
	09/609,303	09/610,095	09/609,596	09/693,705	09/693,647
10	09/721,895	09/721,894	09/607,843	09/693,690	09/607,605
	09/608,178	09/609,553	09/609,233	09/609,149	09/608,022
	09/575,181	09/722,174	09/721,896	10/291,522	10/291,517
	10/291,523	10/291,471	10/291,470	10/291,819	10/291,481
	10/291,509	10/291,825	10/291,519	10/291,575	10/291,557
15	10/291,661	10/291,558	10/291,587	10/291,818	10/291,576
	10/291,589	10/291,526	6,644,545	6,609,653	6,651,879

	10/291,555	10/291,510	19/291,592	10/291,542	10/291,820
	10/291,516	10/291,363	10/291,487	10/291,520	10/291,521
	10/291,556	10/291,821	10/291,525	10/291,586	10/291,822
	10/291,524	10/291,553	10/291,511	10/291,585	10/291,374
5	10/685,523	10/685,583	10/685,455	10/685,584	NPA133US
	09/575,193	09/575,156	09/609,232	09/607,844	09/607,657
	09/693,593	NPB008US	09/928,055	09/927,684	09/928,108
	09/927,685	09/927,809	09/575,183	09/575,160	09/575,150
	09/575,169	6,644,642	6,502,614	6,622,999	09/575,149
10	10/322,450	6,549,935	NPN004US	09/575,187	09/575,155
	6,591,884	6,439,706	09/575,196	09/575,198	09/722,148
	09/722,146	09/721,861	6,290,349	6,428,155	09/575,146
	09/608,920	09/721,892	09/722,171	09/721,858	09/722,142
	10/171,987	10/202,021	10/291,724	10/291,512	10/291,554
15	10/659,027	10/659,026	09/693,301	09/575,174	09/575,163
	09/693,216	09/693,341	09/693,473	09/722,087	09/722,141
	09/722,175	09/722,147	09/575,168	09/722,172	09/693,514
	09/721,893	09/722,088	10/291,578	10/291,823	10/291,560
	10/291,366	10/291,503	10/291,469	10/274,817	09/575,154
20	09/575,129	09/575,124	09/575,188	09/721,862	10/120,441
	10/291,577	10/291,718	10/291,719	10/291,543	10/291,494
	10/292,608	10/291,715	10/291,559	10/291,660	10/409,864
	10/309,358	10/410,484	10/683,151	10/683,040	09/575,189
	09/575,162	09/575,172	09/575,170	09/575,171	09/575,161
25	10/291,716	10/291,547	10/291,538	10/291,717	10/291,827
	10/291,548	10/291,714	10/291,544	10/291,541	10/291,584
	10/291,579	10/291,824	10/291,713	10/291,545	10/291,546
	09/693,388	09/693,704	09/693,510	09/693,336	09/693,335
	10/181,496	10/274,119	10/309,185	10/309,066	NPW014US
30	NPS047US	NPS048US	NPS049US	NPS050US	NPS051US
	NPS052US	NPS053US	NPS054US	NPS045US	NPS046US
	NPT037US	NPA138US	NPA136US		

35 Some applications are temporarily identified by their docket number. This will be replaced by the corresponding application number when available.

In general, the netpageNETPAGE system relies on the production of, and human interaction with, netpagesNETPAGES. These are pages of text, graphics and images printed on ordinary paper, but which work like interactive web pages. Information is encoded on each page using ink which is substantially invisible to the unaided human eye. The ink, however, and thereby the coded data, can be sensed by an optically imaging pen and transmitted to the netpageNETPAGE system.

Active buttons and hyperlinks on each page may be clicked with the pen to request information from the network or to signal preferences to a network server. In some forms, text written by hand on a netpageNETPAGE may be automatically recognized and converted to computer text in the netpageNETPAGE system, allowing forms to be filled in. In other forms, signatures recorded on a netpageNETPAGE may be automatically verified, allowing e-commerce transactions to be securely authorized.

NetpagesNETPAGES are the foundation on which a netpageNETPAGE network is built. They may provide a paper-based user interface to published information and interactive services.

A netpageNETPAGE consists of a printed page (or other surface region) invisibly tagged with references to an online description of the page. The online page description is maintained persistently by a netpageNETPAGE page server. The page description describes the visible layout and content of the page, including text, graphics and images. It also describes the input elements on the page, including buttons, hyperlinks, and input fields. A netpageNETPAGE allows markings made with a netpageNETPAGE pen on its surface to be simultaneously captured and processed by the netpageNETPAGE system.

Multiple netpagesNETPAGES can share the same page description. However, to allow input through otherwise identical pages to be distinguished, each netpageNETPAGE is assigned a unique page identifier. This page ID has sufficient precision to distinguish between a very large number of netpagesNETPAGES.

Each reference to the page description is encoded in a printed tag. The tag identifies the unique page on which it appears, and thereby indirectly identifies the page description. The tag also identifies its own position on the page.

Tags are printed in infrared-absorptive ink on any substrate which is infrared-reflective, such as ordinary paper. Near-infrared wavelengths are invisible to the human eye but are easily sensed by a solid-state image sensor with an appropriate filter.

A tag is sensed by an area image sensor in the netpageNETPAGE pen, and the tag data is transmitted to the netpageNETPAGE system via the nearest netpageNETPAGE printer. The pen is wireless and communicates with the netpageNETPAGE printer via a short-range radio link. Tags are sufficiently small and densely arranged that the pen can reliably image at least one tag even on a single click on the page. It is important that the pen recognize the page ID and position on every interaction with the page, since the interaction is stateless. Tags are error-correctably encoded to make them partially tolerant to surface damage.

The netpageNETPAGE page server maintains a unique page instance for each printed netpageNETPAGE, allowing it to maintain a distinct set of user-supplied values for input fields in the page description for each printed netpageNETPAGE.

Hyperlabel™ is a trade mark of Silverbrook Research Pty Ltd, Australia. In general, Hyperlabel™ systems use an invisible (*e.g.* infrared) tagging scheme to uniquely identify a product item. This has the significant advantage that it allows the entire surface of a product to be tagged, or a significant portion thereof, without impinging on the graphic design of the product's packaging or labeling. If the entire surface of a product is tagged

5 ("omnitagged"), then the orientation of the product does not affect its ability to be scanned *i.e.* a significant part of the line-of-sight disadvantage of visible barcodes is eliminated. Furthermore, if the tags are compact and massively replicated ("omnitags"), then label damage no longer prevents scanning.

Thus, hyperlabelling consists of covering a large portion of the surface of a product with optically-readable invisible tags. When the tags utilize reflection or absorption in the infrared spectrum, they are referred to

10 as infrared identification (IRID) tags. Each Hyperlabel™ tag uniquely identifies the product on which it appears. The tag may directly encode the product code of the item, or it may encode a surrogate ID which in turn identifies the product code via a database lookup. Each tag also optionally identifies its own position on the surface of the product item, to provide the downstream consumer benefits of ~~netpage~~NETPAGE interactivity.

Hyperlabels™ are applied during product manufacture and/or packaging using digital printers, preferably inkjet printers. These may be add-on infrared printers, which print the tags after the text and graphics have been printed by other means, or integrated colour and infrared printers which print the tags, text and graphics simultaneously.

15

Hyperlabels™ can be detected using similar technology to barcodes, except using a light source having an appropriate near-IR frequency. The light source may be a laser (*e.g.* a GaAlAs laser, which emits light at 830 nm) or it may be an LED.

20

From the foregoing, it will be readily apparent that invisible IR detectable inks are an important component of ~~netpage~~NETPAGE and Hyperlabel™ systems. In order for an IR absorbing ink to function satisfactorily in these systems, it should ideally meet a number of criteria:

- (i) compatibility with inkjet printers;
- 25 (ii) compatibility of the IR dye with aqueous solvents used in inkjet inks;
- (iii) intense absorption in the near infra-red region (*e.g.* 700 to 1000 nm);
- (iv) zero or low intensity visible absorption;
- (v) lightfastness;
- (vi) thermal stability;
- 30 (vii) zero or low toxicity;
- (viii) low-cost manufacture;
- (ix) adheres well to paper and other media; and
- (x) no strikethrough and minimal bleeding of the ink on printing.

Hence, it would be desirable to develop IR dyes and ink compositions fulfilling at least some and preferably all of the above criteria. Such inks are desirable to complement ~~netpage~~NETPAGE and Hyperlabel™ systems.

35

Some IR dyes are commercially available from various sources, such as Epolin Products, Avecia Inks and H.W. Sands Corp.

In addition, the prior art describes various IR dyes. US 5,460,646, for example, describes an infrared printing ink comprising a colorant, a vehicle and a solvent, wherein the colorant is a silicon (IV) 2,3-naphthalocyanine bis-trialkylsilyloxi-

US 5,282,894 describes a solvent-based printing ink comprising a metal-free phthalocyanine, a complexed phthalocyanine, a metal-free naphthalocyanine, a complexed naphthalocyanine, a nickel dithiolene, an aminium compound, a methine compound or an azulenesquaric acid.

However, none of the prior art dyes can be formulated into ink compositions suitable for use in ~~netpage~~NETPAGE or Hyperlabel™ systems. In particular, commercially available and/or prior art inks suffer from one or more of the following problems: absorption at wavelengths unsuitable for detection by near-IR sensors; poor solubility or dispersibility in aqueous solvent systems; or unacceptably high absorption in the visible part of the spectrum.


In a typical ~~netpage~~NETPAGE, there may be a large number of hyperlinks on one page and correspondingly relatively large areas of the page printed with IR ink. In the Hyperlabel™ system, the majority of a product's packaging may be printed with the invisible ink. Thus, it is especially desirable that the ink used is invisible to the unaided eye and contains minimal residual colour.

Moreover, inkjet printing is the preferred means for generating ~~netpages~~NETPAGES and Hyperlabels™. Inkjet printing is preferred primarily for its high-speed and low cost. Inkjet inks are typically water-based for reasons of low cost, low toxicity and low flammability. In thermal bubble-jet printers, the ink needs to be rapidly vaporized during the printing process. This rapid vaporization of the ink during the printing process necessitates a water-based ink composition. Accordingly, it is desirable that the IR dyes used in ~~netpage~~NETPAGE and Hyperlabel™ inks are suitable for formulating into aqueous ink compositions and are compatible with inkjet printers.

A further essential requirement of IR dyes used in ~~netpage~~NETPAGE systems is that they must absorb IR radiation at a frequency complementary to the frequency of the IR sensor in the ~~netpage~~NETPAGE pen. Preferably, the ink should contain a dye, which absorbs strongly at the frequency of the IR sensor. Accordingly, the dyes used in ~~netpage~~NETPAGE systems should absorb strongly in the near-IR region – that is, 700 to 1000 nm, preferably 750 to 900 nm, more preferably 780 to 850 nm.

Summary of the Invention

In a first aspect, the present invention provides an IR-absorbing dye suitable for formulating a water-based inkjet ink, said dye being of formula (I):



wherein:

M is selected from Ni, Pd or Pt (preferably Ni);

5 R^{10} and R^{11} are independently selected from C_{1-30} hydrocarbyl, or R^{10} and R^{11} together are joined to form a C_{2-30} hydrocarbylene group;

R^{12} and R^{13} are independently selected from C_{1-30} hydrocarbyl, or R^{12} and R^{13} together are joined to form a C_{2-30} hydrocarbylene group;

wherein at least one of R^{10} , R^{11} , R^{12} or R^{13} comprises a hydrophilic group.

10 In a second aspect, the present invention provides an inkjet ink comprising a dye as described above.

In a third aspect, the present invention provides an inkjet printer comprising a printhead in fluid communication with at least one ink reservoir, wherein said at least one ink reservoir comprises an inkjet ink as described above.

15 In a fourth aspect, the present invention provides an ink cartridge for an inkjet printer, wherein said ink cartridge comprises an inkjet ink as described above.

In a fifth aspect, the present invention provides a substrate having a dye as described above disposed thereon.

20 In a sixth aspect, there is provided a method of enabling entry of data into a computer system via a printed form, the form containing human-readable information and machine-readable coded data, the coded data being indicative of an identity of the form and of a plurality of reference points of the form, the method including the steps of:

receiving, in the computer system and from a sensing device, indicating data regarding the identity of the form and a position of the sensing device relative to the form, the sensing device, when placed in an operative position relative to the form, generating the indicating data using at least some of the coded data;

25 identifying, in the computer system and from the indicating data, at least one field of the form; and

interpreting, in the computer system, at least some of the indicating data as it relates to the at least one field,

wherein said coded data comprises an IR-absorbing dye as described above.

30 In a seventh aspect, there is provided a method of enabling entry of data into a computer system via a printed form, the form containing human-readable information and machine-readable coded data, the coded data being indicative of at least one field of the form, the method including the steps of:

receiving, in the computer system and from a sensing device, indicating data regarding the at least one field and including movement data regarding movement of the sensing device relative to the form, the sensing device, when moved relative to the form, generating the data regarding said at least one field using at least some of the coded data and generating the data regarding its own movement relative to the form; and

5 interpreting, in the computer system, at least some of said indicating data as it relates to said at least one field,

wherein said coded data comprises an IR-absorbing dye as described above.

In an eighth aspect, there is provided a method of enabling entry of data into a computer system via a product item, the product item having a printed surface containing human-readable information and machine-readable coded data, the coded data being indicative of an identity of the product item, the method including the steps of:

(a) receiving, in the computer system and from a sensing device, indicating data regarding the identity of the product item, the sensing device, when placed in an operative position relative to the product item, generating the indicating data using at least some of the coded data; and

15 (b) recording, in the computer system and using the indicating data, information relating to the product item, wherein said coded data comprises an IR-absorbing dye as described above.

In a ninth aspect, there is provided a method of enabling retrieval of data from a computer system via a product item, the product item having a printed surface containing human-readable information and machine-readable coded data, the coded data being indicative of an identity of the product item, the method including the steps of:

(a) receiving, in the computer system and from a sensing device, indicating data regarding the identity of the product item, the sensing device, when placed in an operative position relative to the product item, generating the indicating data using at least some of the coded data;

(b) retrieving, in the computer system and using the indicating data, information relating to the product item; and

25 (c) outputting, from the computer system and to an output device, the information relating to the product item, the output device selected from the group comprising a display device and a printing device, wherein said coded data comprises an IR-absorbing dye as described above.

This disclosure also includes:

30 1. A stabilized ink composition comprising an IR-absorbing metal-dithiolene dye and a singlet oxygen quencher.

2. A method of minimizing absorption of visible light in an ink composition comprising an IR-absorbing metal-dithiolene dye, comprising preselecting said dye such that it includes at least one moiety for reducing intermolecular interactions between adjacent dye molecules.

Brief Description of Drawings

Figure 1 is a schematic of a the relationship between a sample printed netpageNETPAGE and its online page description;

Figure 2 is a schematic view of a interaction between a netpageNETPAGE pen, a Web terminal, a netpageNETPAGE printer, a netpageNETPAGE relay, a netpageNETPAGE page server, and a netpageNETPAGE application server, and a Web server;

Figure 3 illustrates a collection of netpageNETPAGE servers, Web terminals, printers and relays interconnected via a network;

Figure 4 is a schematic view of a high-level structure of a printed netpageNETPAGE and its online page description;

Figure 5a is a plan view showing the interleaving and rotation of the symbols of four codewords of the tag;

Figure 5b is a plan view showing a macrodot layout for the tag shown in Figure 5a;

Figure 5c is a plan view showing an arrangement of nine of the tags shown in Figures 5a and 5b, in which targets are shared between adjacent tags;

Figure 5d is a plan view showing a relationship between a set of the tags shown in Figure 5a and a field of view of a netpageNETPAGE sensing device in the form of a netpageNETPAGE pen;

Figure 6 is a perspective view of a netpageNETPAGE pen and its associated tag-sensing field-of-view cone;

Figure 7 is a perspective exploded view of the netpageNETPAGE pen shown in Figure 6;

Figure 8 is a schematic block diagram of a pen controller for the netpageNETPAGE pen shown in Figures 6 and 7;

Figure 9 is a perspective view of a wall-mounted netpageNETPAGE printer;

Figure 10 is a section through the length of the netpageNETPAGE printer of Figure 9;

Figure 10a is an enlarged portion of Figure 10 showing a section of the duplexed print engines and glue wheel assembly;

Figure 11 is a detailed view of the ink cartridge, ink, air and glue paths, and print engines of the netpageNETPAGE printer of Figures 9 and 10;

Figure 12 is an exploded view of an ink cartridge;

Figure 13 is a schematic view of the structure of an item ID;

Figure 14 is a schematic view of the structure of an omnitag;

Figure 15 is a schematic view of a pen class diagram;

Figure 16 is a schematic view of the interaction between a product item, a fixed product scanner, a hand-held product scanner, a scanner relay, a product server, and a product application server;

Figure 17 is a schematic cross-sectional view through an ink chamber of a unit cell of an inkjet printhead.

Figure 18 shows an absorption spectrum of a dye prepared according to Example 1.

Figure 19 shows an absorption spectrum of a dye prepared according to Example 2.

Figure 20 shows an absorption spectrum of a dye prepared according to Example 3.

Detailed Description

IR-Absorbing Dye

As used herein, the term “IR-absorbing dye” means a dye substance, which absorbs infrared radiation and which is therefore suitable for detection by an infrared sensor. Preferably, the IR-absorbing dye absorbs in the near infrared region, and preferably has a λ_{max} in the range of 700 to 1000 nm, more preferably 750 to 900 nm, more preferably 780 to 850 nm. Dyes having a λ_{max} in this range are particularly suitable for detection by semiconductor lasers, such as a gallium aluminium arsenide diode laser.

Preferably, the hydrophilic group is selected from a hydrophilic polymer chain; an ammonium group; an acid group including salts thereof; or a sulfonamide group.

An example of a hydrophilic polymeric chain is a PEG chain, which may comprise from 2 to 5000 repeating units of ethylene glycol. Other hydrophilic polymer chains will be readily apparent to the person skilled in the art. The hydrophilic polymer chain may be a substituent (or part of a substituent) on the dye molecule.

An ammonium group may be present as a substituent comprising a group of general formula $\text{N}^+(\text{R}^a)(\text{R}^b)(\text{R}^c)$ or $-\text{U}$, wherein R^a , R^b , R^c may be the same or different and are independently selected from H, C_{1-8} alkyl (e.g. methyl, ethyl, cyclohexyl, cyclopentyl, *tert*-butyl, *iso*-propyl etc.), C_{6-12} arylalkyl (e.g. benzyl, phenylethyl etc.) or C_{6-12} aryl (e.g. phenyl, naphthyl etc.); and U is pyridinium, imidazolinium or pyrrolinium. Alternatively, the ammonium group may be present in the form of a quaternarized N atom in the dye molecule. For example, a heteroaromatic N atom in the dye molecule may be quaternarized with a C_{1-8} alkyl or a C_{6-12} arylalkyl group, in accordance with known procedures.

An acid group may be present as a substituent comprising a group of formula $-\text{CO}_2\text{Z}$, $-\text{SO}_3\text{Z}$, $-\text{OSO}_3\text{Z}$, $-\text{PO}_3\text{Z}_2$ or $-\text{OPO}_3\text{Z}_2$, wherein Z is H or a water-soluble cation. Preferably, Z is selected from Li^+ , Na^+ or K^+ . Methods of introducing acid groups, such as those described above, will be well known to the person skilled in the art. For example, a carboxylic acid group may be introduced by oxidation of an olefinic or hydroxyl group in the dye molecule. Alternatively, a sulfonic acid group ($-\text{SO}_3\text{H}$) may be introduced to an aromatic moiety in the dye molecule by sulfonation using, for example, oleum or chlorosulfonic acid. Conversion of the acid group to its salt form can be effected using, for example, a metal hydroxide reagent (e.g. LiOH, NaOH or KOH) or a metal bicarbonate (e.g. NaHCO_3). Non-metal salts may also be prepared using, for example, an ammonium hydroxide (e.g. Bu_4NOH , NH_4OH etc.).

A sulfonamide group may be present as a substituent comprising a group of general formula $-\text{SO}_2\text{NR}^p\text{R}^q$, wherein R^p and R^q are independently selected from H, C_{1-8} alkyl (e.g. methyl, ethyl, cyclohexyl, cyclopentyl, *tert*-butyl, *iso*-propyl etc.), C_{6-12} arylalkyl (e.g. benzyl, phenylethyl etc.) or C_{6-12} aryl (e.g. phenyl, naphthyl etc.).

Preferably, at least one of R^{10} , R^{11} , R^{12} or R^{13} comprises a group or moiety for reducing intermolecular interactions. It has been recognized by the present inventors that IR-absorbing dye compounds of the prior art absorb, at least to some extent, in the visible region of the spectrum. Indeed, the vast majority of IR-absorbing dye

compounds known in the prior art are black. This visible absorption is clearly undesirable in “invisible” IR inks, especially IR inks for use in ~~netpage~~NETPAGE or Hyperlabel™ systems.

It has further been recognized by the present inventors that the presence of visible bands in the IR spectra of IR-absorbing dye compounds, and particularly IR-absorbing metal-ligand complexes, is mainly due to
5 intermolecular interactions between adjacent molecules.

Typically, IR-absorbing compounds comprise a π -system which forms a substantially planar moiety in at least part of the molecule. There is a natural tendency for planar π -systems in adjacent molecules to stack on top of each other *via* intermolecular π -interactions, known as π - π stacking. Hence, IR-absorbing compounds have a natural tendency to group together *via* intermolecular π -interactions, producing relatively weakly bound dimers,
10 trimers *etc.* Without wishing to be bound by theory, it is understood by the present inventors that π - π stacking of IR-absorbing compounds contributes significantly to the production of visible absorption bands in their IR spectra, which would not otherwise be present in the corresponding monomeric compounds. This visible absorption is understood to be due to broadening of IR absorption bands when π -systems stack on top of each other and π -orbitals interact, producing small changes in their respective energy levels. Broadening of IR
15 absorption bands is undesirable in two respects: firstly, it reduces the intensity of absorption in the IR region; secondly, the IR absorption band tends to tail into the visible region, producing highly coloured compounds.

Furthermore, the formation of coloured dimers, trimers *etc.* *via* π - π interactions occurs both in the solid state and in solution. However, it is a particular problem in the solid state, where there are no solvent molecules to disrupt the formation of extended π -stacked oligomers. IR dyes having acceptable solution characteristics may
20 still be intensely coloured solids when printed onto paper. The ideal “invisible” IR dye should remain invisible when the solvent has evaporated or wicked into the paper.

Additionally, the interaction of π -orbitals with local charges or partially charged atoms, such as ions, can be large and this may introduce additional absorption in the visible region.

None of the prior art addresses the problem of visible absorption in IR inks by designing and
25 synthesizing dye molecules specifically adapted to reduce intermolecular interactions in the form of π - π stacking.

Specific examples of moieties suitable for reducing intermolecular interactions are described in more detail below. However, it will be appreciated from the above that any moiety or group that can interfere sufficiently with the intermolecular π - π interactions of adjacent dye molecules will be suitable for minimizing visible absorption, and will therefore be suitable for use in the present invention.

Generally, it is preferable to configure the dye molecule such that the average distance between the π -systems of adjacent molecules is greater than about 3.5 Å, more preferably greater than about 4 Å, and more preferably greater than about 5 Å. This preferred distance between the π -systems of adjacent molecules is based on theoretical calculations. From theoretical studies by the present inventors, it is understood that π - π interactions are significant at a distance of about 3.5 Å or less.
30

Preferably, the moiety for reducing intermolecular interactions extends out of a major plane of the dye molecule. Metal dithiolene dyes typically comprise a π -system of a central metal atom, four S atoms and two carbon-carbon double bonds, which form a major plane of the molecule. The moiety for reducing intermolecular interactions is preferably configured, or can at least fold into a conformation, such that it extends out of this plane and exert steric repulsion on neighbouring dye molecules. The greater the moiety extends out of the plane of the π -system, the greater the reduction in intermolecular interactions will be.

Preferably, the moiety for reducing intermolecular interactions has three-dimensional structure. By “three-dimensional structure”, it is meant that the moiety occupies a volume of three-dimensional space in all conformations. Preferably, the moiety is a three-dimensional C_{3-30} hydrocarbyl or C_{3-30} hydrocarbylene group.

As will be apparent to a person skilled in the art, the exact nature of the three-dimensional hydrocarbyl or hydrocarbylene group is not crucial to the present invention, provided that the group has sufficient three-dimensional structure to inhibit intermolecular interactions. However, preferred moieties suitable for reducing intermolecular interactions are bridged C_{4-30} cyclic groups.

As an alternative (or in addition to) the dye molecule comprising a three-dimensional hydrocarbyl or hydrocarbylene group, the molecule may comprise one or more polymeric substituents for reducing intermolecular interactions. In the context of the present invention, the term “polymeric” is used to describe a group having 2 or more repeating monomer units. For example, the polymeric substituent for reducing intermolecular interactions may comprise from 2 to 5000 repeating monomer units, more preferably 2 to 1000, more preferably 2 to 100, and more preferably 2 to 50.

Without wishing to be bound by theory, it is understood by the present inventors that polymeric substituents, especially polymeric substituents positioned at the periphery of the molecule, interfere with π - π interactions by folding into conformations where at least part of the polymer is positioned between π -systems of adjacent dye molecules. This inhibits intermolecular π - π interactions and hence polymeric substituents, especially peripheral polymeric substituents, reduce the propensity for π -systems to overlap and interact.

It will be readily apparent that the exact nature of the polymeric substituent(s) is not crucial provided that it is able to provide steric repulsion. Accordingly, the substituent may comprise any type of polymer, such as polyethers, polyesters, polyamides, polyurethanes, polyalkenes *etc.*


The polymeric group may comprise a plurality of polymer chains in the form of a dendrimer – that is, a central core or template having a plurality of polymer chains radiating therefrom. The branched nature of dendrimer molecules means that their polymeric chains are able to occupy a large volume in three-dimensional space. This large three-dimensional volume is advantageous for increasing the steric repulsion between respective dye molecules and, hence, reducing intermolecular interactions.

In addition to providing steric repulsion, the polymeric substituent may confer additional properties on the dye molecule. For example, with appropriate selection of the polymeric substituent, it may be used to impart hydrophilic properties on the molecule. Polymeric substituents comprising repeating units of ethylene glycol (a

PEG chain) are particularly suitable for providing hydrophilicity, as well as reducing intermolecular π -interactions.

Preferably, R^{10} and R^{11} together are joined to form a bridged cyclic group. Preferably, R^{12} and R^{13} together are also joined to form a bridged cyclic group. When the dye molecule has two bridged cyclic ligands, the bridging groups are preferably oriented in opposite directions. This maximizes their steric repulsive effect, since both faces of the molecule are effectively “protected” from adjacent dye molecules.

In a particularly preferred embodiment, the dye is of formula (II):



wherein:

M is selected from Ni, Pd or Pt (preferably Ni);

j is selected from 0, 1, 2, 3 or 4;

k is selected from 0, 1, 2, 3 or 4;

n is 1, 2 or 3;

W is a hydrophilic group;

up to three $-(CH_2)-$ groups in the carbocycle may be optionally replaced by a group independently selected from $-C(O)-$, $-NH-$, $-S-$, $-O-$;

up to three $-CH-$ groups in the carbocycle may be optionally replaced by $-N-$;

up to four H atoms in the carbocycle may be optionally replaced by a group independently selected from C_{1-6} alkyl, C_{1-6} alkoxy, C_{6-12} aryl, C_{6-12} arylalkyl, halogen, hydroxyl or amino; and provided that at least one of j or k is greater than 0.


This preferred dye is characterized in that the dithiolene ligands are carbocycles, preferably bridged carbocycles.

Preferably, both j and k are greater than or equal to 1. In one preferred form, j is 1 and k is 2. Further, the dye molecule preferably comprises $-C(Me)_2-$ bridging groups. Preferably, the ligands are bornyl or camphor derivatives. Bornyl or camphor derivatives are advantageous, since they are readily available commercially at relatively low cost.

The group(s) represented by W imparts hydrophilicity to the dye molecule. Preferably, W is selected from a substituent comprising a PEG chain; a substituent comprising an ammonium group; a substituent comprising an acid group, including salts thereof; or a substituent comprising a sulfonamide group. W may be any one of the preferred hydrophilic groups described in detail above. Preferably, W is of formula $-(CH_2)_t-SO_3Z$,

wherein t is 0 or an integer from 1 to 6, and Z is H or a water-soluble cation. More preferably, W is of formula $-\text{CH}_2\text{SO}_3\text{H}$, $-\text{CH}_2\text{SO}_3\text{Na}$ or $-\text{CH}_2\text{SO}_3\text{K}$.

A particularly preferred dye molecule according to the present invention is shown in formula (III) below:



This compound has excellent water-dispersibility combined with minimal absorption in the visible region of the spectrum. It absorbs strongly in the near infrared region at a λ_{max} of 781 nm.

The term “hydrocarbyl” is used herein to refer to monovalent groups consisting generally of carbon and hydrogen. Hydrocarbyl groups thus include alkyl, alkenyl and alkynyl groups (in both straight and branched chain forms), carbocyclic groups (including polycycloalkyl groups such as bicyclooctyl and adamantyl) and aryl groups, and combinations of the foregoing, such as alkylcycloalkyl, alkylpolycycloalkyl, alkylaryl, alkenylaryl, alkynylaryl, cycloalkylaryl and cycloalkenylaryl groups. Similarly, the term “hydrocarbylene” refers to divalent groups corresponding to the monovalent hydrocarbyl groups described above.

Unless specifically stated otherwise, up to four $-\text{C}-\text{C}-$ and/or $-\text{C}-\text{H}$ moieties in the hydrocarbyl group may be optionally interrupted by one or more moieties selected from $-\text{O}-$; $-\text{NR}''-$; $-\text{S}-$; $-\text{C}(\text{O})-$; $-\text{C}(\text{O})\text{O}-$; $-\text{C}(\text{O})\text{NR}''-$; $-\text{S}(\text{O})-$; $-\text{SO}_2-$; $-\text{SO}_2\text{O}-$; $-\text{SO}_2\text{NR}''-$; where R'' is a group selected from H, C_{1-12} alkyl, C_{6-12} aryl or C_{6-12} arylalkyl.

Unless specifically stated otherwise, where the hydrocarbyl group contains one or more $-\text{C}=\text{C}-$ moieties, up to four $-\text{C}=\text{C}-$ moieties may optionally be replaced by $-\text{C}=\text{N}-$. Hence, the term “hydrocarbyl” may include moieties such as heteroaryl, ether, thioether, carboxy, hydroxyl, alkoxy, amine, thiol, amide, ester, ketone, sulfoxide, sulfonate, sulfonamide *etc.*

Unless specifically stated otherwise, the hydrocarbyl group may comprise up to four substituents independently selected from halogen, cyano, nitro, a hydrophilic group as defined above (*e.g.* $-\text{SO}_3\text{H}$, $-\text{SO}_3\text{K}$, $-\text{CO}_2\text{Na}$, $-\text{NH}_3^+$, $-\text{NMe}_3^+$ *etc.*) or a polymeric group as defined above (*e.g.* a polymeric group derived from polyethylene glycol).

As used herein, the term “bridged cyclic group” includes C_{4-30} carbocycles (preferably C_{6-20} carbocycles) containing 1, 2, 3 or 4 bridging atoms. Examples of bridged carbocyclic groups are bornyl and triptycenyl, and derivatives thereof. The term “bridged cyclic group” also includes bridged polycyclic groups, including groups such as adamantanyl and tricyclo[5.2.1.0]decanyl, and derivatives thereof.

Unless specifically stated otherwise, the term “bridged cyclic group” also includes bridged carbocycles wherein 1, 2, 3 or 4 carbon atoms are replaced by heteroatoms selected from N, S or O (*i.e.* bridged heterocycles). When it is stated that a carbon atom in a carbocycle is replaced by a heteroatom, what is meant is that –CH– is replaced by –N–, –CH₂– is replaced by –O–, or –CH₂– is replaced by –S–. Hence, the term “bridged cyclic group” includes bridged heterocyclic groups, such as quinuclidinyl and tropanyl. Unless specifically stated otherwise, any of the bridged cyclic groups may be optionally substituted with 1, 2, 3 or 4 of the substituents described below.

The term “aryl” is used herein to refer to an aromatic group, such as phenyl, naphthyl or triptycenyl. The term “arylene”, of course, refers to divalent groups corresponding to the monovalent aryl groups described above. Any reference to aryl implicitly includes arylene, where appropriate.

The term “heteroaryl” refers to an aryl group, where 1, 2, 3 or 4 carbon atoms are replaced by a heteroatom selected from N, O or S. Examples of heteroaryl (or heteroaromatic) groups include pyridyl, benzimidazolyl, indazolyl, quinolinyl, isoquinolinyl, indolyl, isoindolyl, indolyl, isoindolyl, furanyl, thiophenyl, pyrrolyl, thiazolyl, imidazolyl, oxazolyl, isoxazolyl, pyrazolyl, isoxazolonyl, piperazinyl, pyrimidinyl, piperidinyl, morpholinyl, pyrrolidinyl, isothiazolyl, triazolyl, oxadiazolyl, thiadiazolyl, pyridyl, pyrimidinyl, benzopyrimidinyl, benzotriazole, quinoxalyl, pyridazyl, coumarinyl *etc.* The term “heteroarylene”, of course, refers to divalent groups corresponding to the monovalent heteroaryl groups described above. Any reference to heteroaryl implicitly includes heteroarylene, where appropriate.

Unless specifically stated otherwise, aryl, arylene, heteroaryl and heteroarylene groups may be optionally substituted with 1, 2, 3, 4 or 5 of the substituents described below.

Where reference is made to optionally substituted groups (*e.g.* in connection with bridged cyclic groups, aryl groups or heteroaryl groups), the optional substituent(s) are independently selected from C₁₋₈ alkyl, C₁₋₈ alkoxy, cyano, halogen, amino, hydroxyl, thiol, –SR^u, –NR^uR^v, nitro, phenyl, phenoxy, –CO₂R^v, –C(O)R^v, –OCOR^v, –SO₂R^v, –OSO₂R^v, –SO₂OR^v, –NHC(O)R^v, –CONR^uR^v, –CONR^uR^v, –SO₂NR^uR^v, wherein R^u and R^v are independently selected from hydrogen, C₁₋₁₂ alkyl, phenyl or phenyl-C₁₋₈ alkyl (*e.g.* benzyl). Where, for example, a group contains more than one substituent, different substituents can have different R^u or R^v groups. For example, a naphthyl group may be substituted with three substituents: –SO₂NHPh, –CO₂Me group and –NH₂.

The term “alkyl” is used herein to refer to alkyl groups in both straight and branched forms. Unless stated otherwise, the alkyl group may be interrupted with 1, 2 or 3 heteroatoms selected from O, N or S. Unless stated otherwise, the alkyl group may also be interrupted with 1, 2 or 3 double and/or triple bonds. However, the term “alkyl” usually refers to alkyl groups having no heteroatom interruptions or double or triple bond interruptions. Where “alkenyl” groups are specifically mentioned, this is not intended to be construed as a limitation on the definition of “alkyl” above.

Where reference is made to, for example, C₁₋₁₂ alkyl, it is meant the alkyl group may contain any number of carbon atoms between 1 and 12. Unless specifically stated otherwise, any reference to “alkyl” means C₁₋₁₂ alkyl, preferably C₁₋₆ alkyl.

The term “alkyl” also includes cycloalkyl groups. As used herein, the term “cycloalkyl” includes cycloalkyl, polycycloalkyl, and cycloalkenyl groups, as well as combinations of these with linear alkyl groups, such as cycloalkylalkyl groups. The cycloalkyl group may be interrupted with 1, 2 or 3 heteroatoms selected from O, N or S. However, the term “cycloalkyl” usually refers to cycloalkyl groups having no heteroatom interruptions.

5 Examples of cycloalkyl groups include cyclopentyl, cyclohexyl, cyclohexenyl, cyclohexylmethyl and adamantyl groups.

The term “arylalkyl” refers to groups such as benzyl, phenylethyl and naphthylmethyl.

The term “halogen” or “halo” is used herein to refer to any of fluorine, chlorine, bromine and iodine.

Usually, however, halogen refers to chlorine or fluorine substituents.

10 Where reference is made to “a substituent comprising ...” (*e.g.* “a substituent comprising a hydrophilic group”, “a substituent comprising an acid group (including salts thereof)”, “a substituent comprising a polymeric chain” *etc.*), the substituent in question may consist entirely or partially of the group specified. For example, “a substituent comprising an acid group (including salts thereof)” may be of formula $-(CH_2)_j-SO_3K$, wherein j is 0 or an integer from 1 to 6. Hence, in this context, the term “substituent” may be, for example, an alkyl group,

15 which has a specified group attached. However, it will be readily appreciated that the exact nature of the substituent is not crucial to the desired functionality, provided that the specified group is present.

Chiral compounds described herein have not been given stereo-descriptors. However, when compounds may exist in stereoisomeric forms, then all possible stereoisomers and mixtures thereof are included (*e.g.* enantiomers, diastereomers and all combinations including racemic mixtures *etc.*).

20 Likewise, when compounds may exist in a number of regioisomeric forms, then all possible regioisomers and mixtures thereof are included.

For the avoidance of doubt, the term “a” (or “an”), in phrases such as “comprising a”, means “at least one” and not “one and only one”. Where the term “at least one” is specifically used, this should not be construed as having a limitation on the definition of “a”.

25 Throughout the specification, the term “comprising”, or variations such as “comprise” or “comprises”, should be construed as including a stated element, integer or step, but not excluding any other element, integer or step.

Inkjet Inks

30 The present invention also provides an inkjet ink. Preferably, the inkjet ink is a water-based inkjet ink.

Water-based inkjet ink compositions are well known in the literature and, in addition to water, may comprise additives, such as co-solvents, biocides, sequestering agents, humectants, pH adjusters, viscosity modifiers, penetrants, wetting agents, surfactants *etc.*

Co-solvents are typically water-soluble organic solvents. Suitable water-soluble organic solvents include

35 C_{1-4} alkyl alcohols, such as ethanol, methanol, butanol, propanol, and 2-propanol; glycol ethers, such as ethylene glycol monomethyl ether, ethylene glycol monoethyl ether, ethylene glycol monobutyl ether, ethylene glycol

monomethyl ether acetate, diethylene glycol monomethyl ether, diethylene glycol monoethyl ether, diethylene glycol mono-n-propyl ether, ethylene glycol mono-isopropyl ether, diethylene glycol mono-isopropyl ether, ethylene glycol mono-n-butyl ether, diethylene glycol mono-n-butyl ether, triethylene glycol mono-n-butyl ether, ethylene glycol mono-t-butyl ether, diethylene glycol mono-t-butyl ether, 1-methyl-1-methoxybutanol, propylene glycol monomethyl ether, propylene glycol monoethyl ether, propylene glycol mono-t-butyl ether, propylene glycol mono-n-propyl ether, propylene glycol mono-isopropyl ether, dipropylene glycol monomethyl ether, dipropylene glycol monoethyl ether, dipropylene glycol mono-n-propyl ether, dipropylene glycol mono-isopropyl ether, propylene glycol mono-n-butyl ether, and dipropylene glycol mono-n-butyl ether; formamide, acetamide, dimethyl sulfoxide, sorbitol, sorbitan, glycerol monoacetate, glycerol diacetate, glycerol triacetate, and sulfolane; or combinations thereof.

Other useful water-soluble organic solvents include polar solvents, such as 2-pyrrolidone, N-methylpyrrolidone, ϵ -caprolactam, dimethyl sulfoxide, sulfolane, morpholine, N-ethylmorpholine, 1,3-dimethyl-2-imidazolidinone and combinations thereof.

The inkjet ink may contain a high-boiling water-soluble organic solvent which can serve as a wetting agent or humectant for imparting water retentivity and wetting properties to the ink composition. Such a high-boiling water-soluble organic solvent includes one having a boiling point of 180°C or higher. Examples of the water-soluble organic solvent having a boiling point of 180°C or higher are ethylene glycol, propylene glycol, diethylene glycol, pentamethylene glycol, trimethylene glycol, 2-butene-1,4-diol, 2-ethyl-1,3-hexanediol, 2-methyl-2,4-pentanediol, tripropylene glycol monomethyl ether, dipropylene glycol monoethyl glycol, dipropylene glycol monoethyl ether, dipropylene glycol monomethyl ether, dipropylene glycol, triethylene glycol monomethyl ether, tetraethylene glycol, triethylene glycol, diethylene glycol monobutyl ether, diethylene glycol monoethyl ether, diethylene glycol monomethyl ether, tripropylene glycol, polyethylene glycols having molecular weights of 2000 or lower, 1,3-propylene glycol, isopropylene glycol, isobutylene glycol, 1,4-butanediol, 1,3-butanediol, 1,5-pentanediol, 1,6-hexanediol, glycerol, erythritol, pentaerythritol and combinations thereof.

The total water-soluble organic solvent content in the inkjet ink is preferably about 5 to 50% by weight, more preferably 10 to 30% by weight, based on the total ink composition.

Other suitable wetting agents or humectants include saccharides (including monosaccharides, oligosaccharides and polysaccharides) and derivatives thereof (*e.g.* maltitol, sorbitol, xylitol, hyaluronic salts, aldonic acids, uronic acids *etc.*)

The inkjet ink may also contains a penetrant for accelerating penetration of the aqueous ink into the recording medium. Suitable penetrants include polyhydric alcohol alkyl ethers (glycol ethers) and/or 1,2-alkyldiols. Examples of suitable polyhydric alcohol alkyl ethers are ethylene glycol monomethyl ether, ethylene glycol monoethyl ether, ethylene glycol monobutyl ether, ethylene glycol monomethyl ether acetate, diethylene glycol monomethyl ether, diethylene glycol monoethyl ether, ethylene glycol mono-n-propyl ether, ethylene glycol mono-isopropyl ether, diethylene glycol mono-isopropyl ether, ethylene glycol mono-n-butyl ether, diethylene glycol mono-n-butyl ether, triethylene glycol mono-n-butyl ether, ethylene glycol mono-t-butyl ether,

diethylene glycol mono-t-butyl ether, 1-methyl-1-methoxybutanol, propylene glycol monomethyl ether, propylene glycol monoethyl ether, propylene glycol mono-t-butyl ether, propylene glycol mono-n-propyl ether, propylene glycol mono-isopropyl ether, dipropylene glycol monomethyl ether, dipropylene glycol monoethyl ether, dipropylene glycol mono-n-propyl ether, dipropylene glycol mono-isopropyl ether, propylene glycol mono-n-butyl ether, and dipropylene glycol mono-n-butyl ether. Examples of suitable 1,2-alkyldiols are 1,2-pentanediol and 1,2-hexanediol. The penetrant may also be selected from straight-chain hydrocarbon diols, such as 1,3-propanediol, 1,4-butanediol, 1,5-pentanediol, 1,6-hexanediol, 1,7-heptanediol, and 1,8-octanediol. Glycerol may also be used as a penetrant.

The amount of penetrant is preferably in the range of 1 to 20% by weight, more preferably 1 to 10% by weight, based on the total ink composition.

The inkjet ink may also contain a surface active agent, especially an anionic surface active agent and/or a nonionic surface active agent. Useful anionic surface active agents include sulfonic acid types, such as alkanesulfonic acid salts, α -olefinsulfonic acid salts, alkylbenzenesulfonic acid salts, alkylnaphthalenesulfonic acids, acylmethyltaurines, and dialkylsulfosuccinic acids; alkylsulfuric ester salts, sulfated oils, sulfated olefins, polyoxyethylene alkyl ether sulfuric ester salts; carboxylic acid types, *e.g.*, fatty acid salts and alkylsarcosine salts; and phosphoric acid ester types, such as alkylphosphoric ester salts, polyoxyethylene alkyl ether phosphoric ester salts, and glycerophosphoric ester salts. Specific examples of the anionic surface active agents are sodium dodecylbenzenesulfonate, sodium laurate, and a polyoxyethylene alkyl ether sulfate ammonium salt.

Suitable nonionic surface active agents include ethylene oxide adduct types, such as polyoxyethylene alkyl ethers, polyoxyethylene alkylphenyl ethers, polyoxyethylene alkyl esters, and polyoxyethylene alkylamides; polyol ester types, such as glycerol alkyl esters, sorbitan alkyl esters, and sugar alkyl esters; polyether types, such as polyhydric alcohol alkyl ethers; and alkanolamide types, such as alkanolamine fatty acid amides. Specific examples of nonionic surface active agents are ethers such as polyoxyethylene nonylphenyl ether, polyoxyethylene octylphenyl ether, polyoxyethylene dodecylphenyl ether, polyoxyethylene alkylallyl ether, polyoxyethylene oleyl ether, polyoxyethylene lauryl ether, and polyoxyalkylene alkyl ethers (*e.g.* polyoxyethylene alkyl ethers); and esters, such as polyoxyethylene oleate, polyoxyethylene oleate ester, polyoxyethylene distearate, sorbitan laurate, sorbitan monostearate, sorbitan mono-oleate, sorbitan sesquioleate, polyoxyethylene mono-oleate, and polyoxyethylene stearate. Acetylene glycol surface active agents, such as 2,4,7,9-tetramethyl-5-decyne-4,7-diol, 3,6-dimethyl-4-octyne-3,6-diol or 3,5-dimethyl-1-hexyn-3-ol, may also be used.

The inkjet ink may contain a pH adjuster for adjusting its pH to 7 to 9. Suitable pH adjusters include basic compounds, such as sodium hydroxide, potassium hydroxide, lithium hydroxide, sodium carbonate, sodium hydrogencarbonate, potassium carbonate, potassium hydrogencarbonate, lithium carbonate, sodium phosphate, potassium phosphate, lithium phosphate, potassium dihydrogenphosphate, dipotassium hydrogenphosphate, sodium oxalate, potassium oxalate, lithium oxalate, sodium borate, sodium tetraborate, potassium hydrogenphthalate, and potassium hydrogentartrate; ammonia; and amines, such as methylamine, ethylamine,

diethylamine, trimethylamine, triethylamine, tris(hydroxymethyl)aminomethane hydrochloride, triethanolamine, diethanolamine, diethylethanolamine, triisopropanolamine, butyldiethanolamine, morpholine, and propanolamine.

The inkjet ink may also include a biocide, such as benzoic acid, dichlorophene, hexachlorophene, sorbic acid, hydroxybenzoic esters, sodium dehydroacetate, 1,2-benthiazolin-3-one, 3,4-isothiazolin-3-one or 4,4-

5 dimethyloxazolidine.

The inkjet ink may also contain a sequestering agent, such as ethylenediaminetetraacetic acid (EDTA).

The inkjet ink may also contain a singlet oxygen quencher. The presence of singlet oxygen quencher(s) in the ink reduces the propensity for the IR-absorbing dye to degrade. The quencher consumes any singlet oxygen generated in the vicinity of the dye molecules and, hence, minimizes their degradation. An excess of singlet
10 oxygen quencher is advantageous for minimizing degradation of the dye and retaining its IR-absorbing properties over time. Preferably, the singlet oxygen quencher is selected from ascorbic acid, 1,4-diazabicyclo-[2.2.2]octane (DABCO), azides (*e.g.* sodium azide), histidine or tryptophan.

Inkjet Printers

15 The present invention also provides an inkjet printer comprising a printhead in fluid communication with at least one ink reservoir, wherein said ink reservoir comprises an inkjet ink as described above.

Inkjet printers, such as thermal bubble-jet and piezoelectric printers, are well known in the art and will form part of the skilled person's common general knowledge. The printer may be a high-speed inkjet printer. The printer is preferably a pagewidth printer. Preferred inkjet printers and printheads for use in the present invention
20 are described in the following patents and patent applications, all of which are incorporated herein by reference in their entirety.

10/302,274	6692108	6672709	10/303,348	6672710	6669334
10/302,668	10/302,577	6669333	10/302,618	10/302,617	10/302,297

25 In one preferred form, the printhead comprises:

a plurality of nozzles;

a bubble forming chamber corresponding to each of the nozzles respectively, the bubble forming chambers adapted to contain ejectable liquid; and

30 a heater element disposed in each of the bubble forming chambers respectively, the heater element configured for thermal contact with the ejectable liquid; such that,

heating the heater element to a temperature above the boiling point of the ejectable liquid forms a gas bubble that causes the ejection of a drop of the ejectable liquid from the nozzle; wherein,

35 the heater element is suspended in the ink chamber such that during use at least a portion of the heater element is encircled by, and in direct contact with, the ejectable fluid.

There now follows a brief description of a printhead suitable for use in the present invention. With reference to Figure 17, the unit cell 1001 of a printhead according to an embodiment of the invention comprises a nozzle plate 1002 with nozzles 1003 therein, the nozzles having nozzle rims 1004, and apertures 1005 extending through the nozzle plate. The nozzle plate 1002 is plasma etched from a silicon nitride structure which is

5 deposited, by way of chemical vapor deposition (CVD), over a sacrificial material which is subsequently etched.

The printhead also includes, with respect to each nozzle 1003, side walls 1006 on which the nozzle plate is supported, a chamber 1007 defined by the walls and the nozzle plate 1002, a multi-layer substrate 1008 and an inlet passage 1009 extending through the multi-layer substrate to the far side (not shown) of the substrate. A looped, elongate heater element 1010 is suspended within the chamber 1007, so that the element is in the form of

10 a suspended beam. The printhead as shown is a microelectromechanical system (MEMS) structure, which is formed by a lithographic process.

When the printhead is in use, ink 1011 from a reservoir (not shown) enters the chamber 1007 via the inlet passage 1009, so that the chamber fills. Thereafter, the heater element 1010 is heated for somewhat less than 1 micro second, so that the heating is in the form of a thermal pulse. It will be appreciated that the heater element

15 1010 is in thermal contact with the ink 1011 in the chamber 1007 so that when the element is heated, this causes the generation of vapor bubbles in the ink. Accordingly, the ink 1011 constitutes a bubble forming liquid.

The bubble 1012, once generated, causes an increase in pressure within the chamber 1007, which in turn causes the ejection of a drop 1016 of the ink 1011 through the nozzle 1003. The rim 1004 assists in directing the drop 1016 as it is ejected, so as to minimize the chance of a drop misdirection.

20 The reason that there is only one nozzle 1003 and chamber 1007 per inlet passage 1009 is so that the pressure wave generated within the chamber, on heating of the element 1010 and forming of a bubble 1012, does not effect adjacent chambers and their corresponding nozzles.

The increase in pressure within the chamber 1007 not only pushes ink 1011 out through the nozzle 1003, but also pushes some ink back through the inlet passage 1009. However, the inlet passage 1009 is approximately

25 200 to 300 microns in length, and is only approximately 16 microns in diameter. Hence there is a substantial viscous drag. As a result, the predominant effect of the pressure rise in the chamber 1007 is to force ink out through the nozzle 1003 as an ejected drop 1016, rather than back through the inlet passage 9.

As shown in Figure 17, the ink drop 1016 is being ejected is shown during its "necking phase" before the drop breaks off. At this stage, the bubble 1012 has already reached its maximum size and has then begun to

30 collapse towards the point of collapse 1017.

The collapsing of the bubble 1012 towards the point of collapse 1017 causes some ink 1011 to be drawn from within the nozzle 1003 (from the sides 1018 of the drop), and some to be drawn from the inlet passage 1009, towards the point of collapse. Most of the ink 1011 drawn in this manner is drawn from the nozzle 1003, forming an annular neck 1019 at the base of the drop 16 prior to its breaking off.

35 The drop 1016 requires a certain amount of momentum to overcome surface tension forces, in order to break off. As ink 1011 is drawn from the nozzle 1003 by the collapse of the bubble 1012, the diameter of the neck

1019 reduces thereby reducing the amount of total surface tension holding the drop, so that the momentum of the drop as it is ejected out of the nozzle is sufficient to allow the drop to break off.

When the drop 1016 breaks off, cavitation forces are caused as reflected by the arrows 1020, as the bubble 1012 collapses to the point of collapse 1017. It will be noted that there are no solid surfaces in the vicinity of the point of collapse 1017 on which the cavitation can have an effect.

Inkjet Cartridges

The present invention also provides an inkjet ink cartridge comprising an inkjet ink as described above. Ink cartridges for inkjet printers are well known in the art and are available in numerous forms. Preferably, the inkjet ink cartridges of the present invention are replaceable. Inkjet cartridges suitable for use in the present invention are described in the following patent and patent application, all of which are incorporated herein by reference in their entirety.

6428155, 10/171,987

In one preferred form, the ink cartridge comprises:

a housing defining a plurality of storage areas wherein at least one of the storage areas contains colorant for printing information that is visible to the human eye and at least one of the other storage areas contains an inkjet ink as described above.

Preferably, each storage area is sized corresponding to the expected levels of use of its contents relative to the intended print coverage for a number of printed pages.

There now follows a brief description of an ink cartridge according to the present invention. Figure 12 shows the complete assembly of the replaceable ink cartridge 627. It has bladders or chambers for storing fixative 644, adhesive 630, and cyan 631, magenta 632, yellow 633, black 634 and infrared 635 inks. The cartridge 627 also contains a micro air filter 636 in a base molding 637. As shown in Figure 9, the micro air filter 636 interfaces with an air pump 638 inside the printer via a hose 639. This provides filtered air to the printheads 705 to prevent ingress of micro particles into the Memjet™ printheads 705 which may clog the nozzles. By incorporating the air filter 636 within the cartridge 627, the operational life of the filter is effectively linked to the life of the cartridge. This ensures that the filter is replaced together with the cartridge rather than relying on the user to clean or replace the filter at the required intervals. Furthermore, the adhesive and infrared ink are replenished together with the visible inks and air filter thereby reducing how frequently the printer operation is interrupted because of the depletion of a consumable material.

The cartridge 627 has a thin wall casing 640. The ink bladders 631 to 635 and fixative bladder 644 are suspended within the casing by a pin 645 which hooks the cartridge together. The single glue bladder 630 is accommodated in the base molding 637. This is a fully recyclable product with a capacity for printing and gluing 3000 pages (1500 sheets).

Substrates

As mentioned above, the dyes of the present invention are especially suitable for use in Hyperlabel™ and ~~netpage~~NETPAGE systems. Such systems are described in more detail below and in the patent applications listed above, all of which are incorporated herein by reference in their entirety.

Hence, the present invention provides a substrate having an IR-absorbing dye as described above disposed thereon. Preferably, the substrate comprises an interface surface. Preferably, the dye is disposed in the form of coded data suitable for use in ~~netpage~~NETPAGE and/or Hyperlabel™ systems. For example, the coded data may be indicative of the identity of a product item. Preferably, the coded data is disposed over a substantial portion of an interface surface of the substrate (*e.g.* greater than 20%, greater than 50% or greater than 90% of the surface).

Preferably, the substrate is IR reflective so that the dye disposed thereon may be detected by a sensing device. The substrate may be comprised of any suitable material such as plastics (*e.g.* polyolefins, polyesters, polyamides *etc.*), paper, metal or combinations thereof.

For ~~netpage~~NETPAGE applications, the substrate is preferably a paper sheet. For Hyperlabel™ applications, the substrate is preferably a tag, a label, a packaging material or a surface of a product item. Typically, tags and labels are comprised of plastics, paper or combinations thereof.

In accordance with Hyperlabel™ applications of the invention, the substrate may be an interactive product item adapted for interaction with a user via a sensing device and a computer system, the interactive product item comprising:

a product item having an identity;

an interface surface associated with the product item and having disposed thereon information relating to the product item and coded data indicative of the identity of the product item, wherein said coded data comprise an IR-absorbing dye as described above.

~~Netpage~~NETPAGE and Hyperlabel™

~~Netpage~~NETPAGE applications of this invention are described generally in the sixth and seventh aspects of the invention above. Hyperlabel™ applications of this invention are described generally in the eighth and ninth aspects of the invention above.

There now follows a detailed overview of ~~netpage~~NETPAGE and Hyperlabel™. (Note: Memjet™ and Hyperlabel™ are trade marks of Silverbrook Research Pty Ltd, Australia). It will be appreciated that not every implementation will necessarily embody all or even most of the specific details and extensions discussed below in relation to the basic system. However, the system is described in its most complete form to reduce the need for external reference when attempting to understand the context in which the preferred embodiments and aspects of the present invention operate.

In brief summary, the preferred form of the ~~netpage~~NETPAGE system employs a computer interface in the form of a mapped surface, that is, a physical surface which contains references to a map of the surface

maintained in a computer system. The map references can be queried by an appropriate sensing device. Depending upon the specific implementation, the map references may be encoded visibly or invisibly, and defined in such a way that a local query on the mapped surface yields an unambiguous map reference both within the map and among different maps. The computer system can contain information about features on the mapped surface, and such information can be retrieved based on map references supplied by a sensing device used with the mapped surface. The information thus retrieved can take the form of actions which are initiated by the computer system on behalf of the operator in response to the operator's interaction with the surface features.

In its preferred form, the netpageNETPAGE system relies on the production of, and human interaction with, netpagesNETPAGES. These are pages of text, graphics and images printed on ordinary paper, but which work like interactive web pages. Information is encoded on each page using ink which is substantially invisible to the unaided human eye. The ink, however, and thereby the coded data, can be sensed by an optically imaging pen and transmitted to the netpageNETPAGE system.

In the preferred form, active buttons and hyperlinks on each page can be clicked with the pen to request information from the network or to signal preferences to a network server. In one embodiment, text written by hand on a netpageNETPAGE is automatically recognized and converted to computer text in the netpageNETPAGE system, allowing forms to be filled in. In other embodiments, signatures recorded on a netpageNETPAGE are automatically verified, allowing e-commerce transactions to be securely authorized.

As illustrated in Figure 1, a printed netpageNETPAGE 1 can represent an interactive form which can be filled in by the user both physically, on the printed page, and "electronically", via communication between the pen and the netpageNETPAGE system. The example shows a "Request" form containing name and address fields and a submit button. The netpageNETPAGE consists of graphic data 2 printed using visible ink, and coded data 3 printed as a collection of tags 4 using invisible ink. The corresponding page description 5, stored on the netpageNETPAGE network, describes the individual elements of the netpageNETPAGE. In particular it describes the type and spatial extent (zone) of each interactive element (i.e. text field or button in the example), to allow the netpageNETPAGE system to correctly interpret input via the netpageNETPAGE. The submit button 6, for example, has a zone 7 which corresponds to the spatial extent of the corresponding graphic 8.

As illustrated in Figure 2, the netpageNETPAGE pen 101, a preferred form of which is shown in Figures 6 and 7 and described in more detail below, works in conjunction with a personal computer (PC), Web terminal 75, or a netpageNETPAGE printer 601. The netpageNETPAGE printer is an Internet-connected printing appliance for home, office or mobile use. The pen is wireless and communicates securely with the netpageNETPAGE network via a short-range radio link 9. Short-range communication is relayed to the netpageNETPAGE network by a local relay function which is either embedded in the PC, Web terminal or netpageNETPAGE printer, or is provided by a separate relay device 44. The relay function can also be provided by a mobile phone or other device which incorporates both short-range and longer-range communications functions.

In an alternative embodiment, the netpageNETPAGE pen utilises a wired connection, such as a USB or other serial connection, to the PC, Web terminal, netpageNETPAGE printer or relay device.

The netpageNETPAGE printer 601, a preferred form of which is shown in Figures 9 to 11 and described in more detail below, is able to deliver, periodically or on demand, personalized newspapers, magazines, catalogs, brochures and other publications, all printed at high quality as interactive netpagesNETPAGES. Unlike a personal computer, the netpageNETPAGE printer is an appliance which can be, for example, wall-mounted adjacent to an area where the morning news is first consumed, such as in a user's kitchen, near a breakfast table, or near the household's point of departure for the day. It also comes in tabletop, desktop, portable and miniature versions.

NetpagesNETPAGES printed at their point of consumption combine the ease-of-use of paper with the timeliness and interactivity of an interactive medium.

As shown in Figure 2, the netpageNETPAGE pen 101 interacts with the coded data on a printed netpageNETPAGE 1 (or product item 201) and communicates the interaction via a short-range radio link 9 to a relay. The relay sends the interaction to the relevant netpageNETPAGE page server 10 for interpretation. In appropriate circumstances, the page server sends a corresponding message to application computer software running on a netpageNETPAGE application server 13. The application server may in turn send a response which is printed on the originating printer.

In an alternative embodiment, the PC, Web terminal, netpageNETPAGE printer or relay device may communicate directly with local or remote application software, including a local or remote Web server. Relatedly, output is not limited to being printed by the netpageNETPAGE printer. It can also be displayed on the PC or Web terminal, and further interaction can be screen-based rather than paper-based, or a mixture of the two.

The netpageNETPAGE system is made considerably more convenient in the preferred embodiment by being used in conjunction with high-speed microelectromechanical system (MEMS) based inkjet (Memjet™) printers. In the preferred form of this technology, relatively high-speed and high-quality printing is made more affordable to consumers. In its preferred form, a netpageNETPAGE publication has the physical characteristics of a traditional newsmagazine, such as a set of letter-size glossy pages printed in full color on both sides, bound together for easy navigation and comfortable handling.

The netpageNETPAGE printer exploits the growing availability of broadband Internet access. Cable service is available to 95% of households in the United States, and cable modem service offering broadband Internet access is already available to 20% of these. The netpageNETPAGE printer can also operate with slower connections, but with longer delivery times and lower image quality. Indeed, the netpageNETPAGE system can be enabled using existing consumer inkjet and laser printers, although the system will operate more slowly and will therefore be less acceptable from a consumer's point of view. In other embodiments, the netpageNETPAGE system is hosted on a private intranet. In still other embodiments, the netpageNETPAGE system is hosted on a single computer or computer-enabled device, such as a printer.

NetpageNETPAGE publication servers 14 on the netpageNETPAGE network are configured to deliver print-quality publications to netpageNETPAGE printers. Periodical publications are delivered automatically to subscribing netpageNETPAGE printers via pointcasting and multicasting Internet protocols. Personalized publications are filtered and formatted according to individual user profiles.

A netpageNETPAGE printer can be configured to support any number of pens, and a pen can work with any number of netpageNETPAGE printers. In the preferred implementation, each netpageNETPAGE pen has a unique identifier. A household may have a collection of colored netpageNETPAGE pens, one assigned to each member of the family. This allows each user to maintain a distinct profile with respect to a netpageNETPAGE publication server or application server.

A netpageNETPAGE pen can also be registered with a netpageNETPAGE registration server 11 and linked to one or more payment card accounts. This allows e-commerce payments to be securely authorized using the netpageNETPAGE pen. The netpageNETPAGE registration server compares the signature captured by the netpageNETPAGE pen with a previously registered signature, allowing it to authenticate the user's identity to an e-commerce server. Other biometrics can also be used to verify identity. A version of the netpageNETPAGE pen includes fingerprint scanning, verified in a similar way by the netpageNETPAGE registration server.

Although a netpageNETPAGE printer may deliver periodicals such as the morning newspaper without user intervention, it can be configured never to deliver unsolicited junk mail. In its preferred form, it only delivers periodicals from subscribed or otherwise authorized sources. In this respect, the netpageNETPAGE printer is unlike a fax machine or e-mail account which is visible to any junk mailer who knows the telephone number or email address.

1 NETPAGE SYSTEM ARCHITECTURE

Each object model in the system is described using a Unified Modeling Language (UML) class diagram. A class diagram consists of a set of object classes connected by relationships, and two kinds of relationships are of interest here: associations and generalizations. An association represents some kind of relationship between objects, i.e. between instances of classes. A generalization relates actual classes, and can be understood in the following way: if a class is thought of as the set of all objects of that class, and class A is a generalization of class B, then B is simply a subset of A. The UML does not directly support second-order modelling - i.e. classes of classes.

Each class is drawn as a rectangle labelled with the name of the class. It contains a list of the attributes of the class, separated from the name by a horizontal line, and a list of the operations of the class, separated from the attribute list by a horizontal line. In the class diagrams which follow, however, operations are never modelled.

An association is drawn as a line joining two classes, optionally labelled at either end with the multiplicity of the association. The default multiplicity is one. An asterisk (*) indicates a multiplicity of "many", i.e. zero or more. Each association is optionally labelled with its name, and is also optionally labelled at either end with the role of the corresponding class. An open diamond indicates an aggregation association ("is-part-of"), and is drawn at the aggregator end of the association line.

A generalization relationship (“is-a”) is drawn as a solid line joining two classes, with an arrow (in the form of an open triangle) at the generalization end.

When a class diagram is broken up into multiple diagrams, any class which is duplicated is shown with a dashed outline in all but the main diagram which defines it. It is shown with attributes only where it is defined.

5 1.1 NETPAGES

NetpagesNETPAGES are the foundation on which a netpageNETPAGE network is built. They provide a paper-based user interface to published information and interactive services.

10 A netpageNETPAGE consists of a printed page (or other surface region) invisibly tagged with references to an online description of the page. The online page description is maintained persistently by a netpageNETPAGE page server. The page description describes the visible layout and content of the page, including text, graphics and images. It also describes the input elements on the page, including buttons, hyperlinks, and input fields. A netpageNETPAGE allows markings made with a netpageNETPAGE pen on its surface to be simultaneously captured and processed by the netpageNETPAGE system.

15 Multiple netpagesNETPAGES can share the same page description. However, to allow input through otherwise identical pages to be distinguished, each netpageNETPAGE is assigned a unique page identifier. This page ID has sufficient precision to distinguish between a very large number of netpagesNETPAGES.

Each reference to the page description is encoded in a printed tag. The tag identifies the unique page on which it appears, and thereby indirectly identifies the page description. The tag also identifies its own position on the page. Characteristics of the tags are described in more detail below.

20 Tags are printed in infrared-absorptive ink on any substrate which is infrared-reflective, such as ordinary paper. Near-infrared wavelengths are invisible to the human eye but are easily sensed by a solid-state image sensor with an appropriate filter.

25 A tag is sensed by an area image sensor in the netpageNETPAGE pen, and the tag data is transmitted to the netpageNETPAGE system via the nearest netpageNETPAGE printer. The pen is wireless and communicates with the netpageNETPAGE printer via a short-range radio link. Tags are sufficiently small and densely arranged that the pen can reliably image at least one tag even on a single click on the page. It is important that the pen recognize the page ID and position on every interaction with the page, since the interaction is stateless. Tags are error-correctably encoded to make them partially tolerant to surface damage.

30 The netpageNETPAGE page server maintains a unique page instance for each printed netpageNETPAGE, allowing it to maintain a distinct set of user-supplied values for input fields in the page description for each printed netpageNETPAGE.

35 The relationship between the page description, the page instance, and the printed netpageNETPAGE is shown in Figure 4. The printed netpageNETPAGE may be part of a printed netpageNETPAGE document 45. The page instance is associated with both the netpageNETPAGE printer which printed it and, if known, the netpageNETPAGE user who requested it.

As shown in Figure 4, one or more ~~netpages~~NETPAGES may also be associated with a physical object such as a product item, for example when printed onto the product item's label, packaging, or actual surface.

1.2 NETPAGE TAGS

1.2.1 Tag Data Content

In a preferred form, each tag identifies the region in which it appears, and the location of that tag within the region. A tag may also contain flags which relate to the region as a whole or to the tag. One or more flag bits may, for example, signal a tag sensing device to provide feedback indicative of a function associated with the immediate area of the tag, without the sensing device having to refer to a description of the region. A ~~netpage~~NETPAGE pen may, for example, illuminate an "active area" LED when in the zone of a hyperlink.

As will be more clearly explained below, in a preferred embodiment, each tag contains an easily recognized invariant structure which aids initial detection, and which assists in minimizing the effect of any warp induced by the surface or by the sensing process. The tags preferably tile the entire page, and are sufficiently small and densely arranged that the pen can reliably image at least one tag even on a single click on the page. It is important that the pen recognize the page ID and position on every interaction with the page, since the interaction is stateless.

In a preferred embodiment, the region to which a tag refers coincides with an entire page, and the region ID encoded in the tag is therefore synonymous with the page ID of the page on which the tag appears. In other embodiments, the region to which a tag refers can be an arbitrary subregion of a page or other surface. For example, it can coincide with the zone of an interactive element, in which case the region ID can directly identify the interactive element.

In the preferred form, each tag contains 120 bits of information. The region ID is typically allocated up to 100 bits, the tag ID at least 16 bits, and the remaining bits are allocated to flags etc. Assuming a tag density of 64 per square inch, a 16-bit tag ID supports a region size of up to 1024 square inches. Larger regions can be mapped continuously without increasing the tag ID precision simply by using abutting regions and maps. The 100-bit region ID allows 2^{100} ($\sim 10^{30}$ or a million trillion trillion) different regions to be uniquely identified.

1.2.2 Tag Data Encoding

In one embodiment, the 120 bits of tag data are redundantly encoded using a (15, 5) Reed-Solomon code. This yields 360 encoded bits consisting of 6 codewords of 15 4-bit symbols each. The (15, 5) code allows up to 5 symbol errors to be corrected per codeword, i.e. it is tolerant of a symbol error rate of up to 33% per codeword.

Each 4-bit symbol is represented in a spatially coherent way in the tag, and the symbols of the six codewords are interleaved spatially within the tag. This ensures that a burst error (an error affecting multiple spatially adjacent bits) damages a minimum number of symbols overall and a minimum number of symbols in any one codeword, thus maximising the likelihood that the burst error can be fully corrected.

Any suitable error-correcting code can be used in place of a (15, 5) Reed-Solomon code, for example: a Reed-Solomon code with more or less redundancy, with the same or different symbol and codeword

sizes; another block code; or a different kind of code, such as a convolutional code (see, for example, Stephen B. Wicker, *Error Control Systems for Digital Communication and Storage*, Prentice-Hall 1995, the contents of which are herein incorporated by reference thereto).

In order to support "single-click" interaction with a tagged region via a sensing device, the sensing device must be able to see at least one entire tag in its field of view no matter where in the region or at what orientation it is positioned. The required diameter of the field of view of the sensing device is therefore a function of the size and spacing of the tags.

1.2.3 Tag Structure

Figure 5a shows a tag 4, in the form of tag 726 with four perspective targets 17. The tag 726 represents sixty 4-bit Reed-Solomon symbols 747, for a total of 240 bits. The tag represents each "one" bit by the presence of a mark 748, referred to as a macrodot, and each "zero" bit by the absence of the corresponding macrodot. Figure 5c shows a square tiling 728 of nine tags, containing all "one" bits for illustrative purposes. It will be noted that the perspective targets are designed to be shared between adjacent tags. Figure 5d shows a square tiling of 16 tags and a corresponding minimum field of view 193, which spans the diagonals of two tags.

Using a (15, 7) Reed-Solomon code, 112 bits of tag data are redundantly encoded to produce 240 encoded bits. The four codewords are interleaved spatially within the tag to maximize resilience to burst errors. Assuming a 16-bit tag ID as before, this allows a region ID of up to 92 bits.

The data-bearing macrodots 748 of the tag are designed to not overlap their neighbors, so that groups of tags cannot produce structures that resemble targets. This also saves ink. The perspective targets allow detection of the tag, so further targets are not required.

Although the tag may contain an orientation feature to allow disambiguation of the four possible orientations of the tag relative to the sensor, the present invention is concerned with embedding orientation data in the tag data. For example, the four codewords can be arranged so that each tag orientation (in a rotational sense) contains one codeword placed at that orientation, as shown in Figure 5a, where each symbol is labelled with the number of its codeword (1-4) and the position of the symbol within the codeword (A-O). Tag decoding then consists of decoding one codeword at each rotational orientation. Each codeword can either contain a single bit indicating whether it is the first codeword, or two bits indicating which codeword it is. The latter approach has the advantage that if, say, the data content of only one codeword is required, then at most two codewords need to be decoded to obtain the desired data. This may be the case if the region ID is not expected to change within a stroke and is thus only decoded at the start of a stroke. Within a stroke only the codeword containing the tag ID is then desired. Furthermore, since the rotation of the sensing device changes slowly and predictably within a stroke, only one codeword typically needs to be decoded per frame.

It is possible to dispense with perspective targets altogether and instead rely on the data representation being self-registering. In this case each bit value (or multi-bit value) is typically represented by an explicit glyph, i.e. no bit value is represented by the absence of a glyph. This ensures that the data grid is well-populated, and thus allows the grid to be reliably identified and its perspective distortion detected and subsequently corrected

during data sampling. To allow tag boundaries to be detected, each tag data must contain a marker pattern, and these must be redundantly encoded to allow reliable detection. The overhead of such marker patterns is similar to the overhead of explicit perspective targets. Various such schemes are described in the present applicants' co-pending PCT application PCT/AU01/01274 filed 11 October 2001.

5 The arrangement 728 of Figure 5c shows that the square tag 726 can be used to fully tile or tessellate, i.e. without gaps or overlap, a plane of arbitrary size.

Although in preferred embodiments the tagging schemes described herein encode a single data bit using the presence or absence of a single undifferentiated macrodot, they can also use sets of differentiated glyphs to represent single-bit or multi-bit values, such as the sets of glyphs illustrated in the present applicants' co-pending PCT application PCT/AU01/01274 filed 11 October 2001.

1.3 THE NETPAGE NETWORK

10 In a preferred embodiment, a netpageNETPAGE network consists of a distributed set of netpageNETPAGE page servers 10, netpageNETPAGE registration servers 11, netpageNETPAGE ID servers 12, netpageNETPAGE application servers 13, netpageNETPAGE publication servers 14, Web terminals 75, netpageNETPAGE printers 601, and relay devices 44 connected via a network 19 such as the Internet, as shown in Figure 3.

15 The netpageNETPAGE registration server 11 is a server which records relationships between users, pens, printers, applications and publications, and thereby authorizes various network activities. It authenticates users and acts as a signing proxy on behalf of authenticated users in application transactions. It also provides handwriting recognition services. As described above, a netpageNETPAGE page server 10 maintains persistent information about page descriptions and page instances. The netpageNETPAGE network includes any number of page servers, each handling a subset of page instances. Since a page server also maintains user input values for each page instance, clients such as netpageNETPAGE printers send netpageNETPAGE input directly to the appropriate page server. The page server interprets any such input relative to the description of the corresponding page.

20 A netpageNETPAGE ID server 12 allocates document IDs 51 on demand, and provides load-balancing of page servers via its ID allocation scheme.

25 A netpageNETPAGE printer uses the Internet Distributed Name System (DNS), or similar, to resolve a netpageNETPAGE page ID 50 into the network address of the netpageNETPAGE page server handling the corresponding page instance.

30 A netpageNETPAGE application server 13 is a server which hosts interactive netpageNETPAGE applications. A netpageNETPAGE publication server 14 is an application server which publishes netpageNETPAGE documents to netpageNETPAGE printers.

35 NetpageNETPAGE servers can be hosted on a variety of network server platforms from manufacturers such as IBM, Hewlett-Packard, and Sun. Multiple netpageNETPAGE servers can run concurrently on a single host, and a single server can be distributed over a number of hosts. Some or all of the functionality provided by

netpageNETPAGE servers, and in particular the functionality provided by the ID server and the page server, can also be provided directly in a netpageNETPAGE appliance such as a netpageNETPAGE printer, in a computer workstation, or on a local network.

1.4 THE NETPAGE PRINTER

The netpageNETPAGE printer 601 is an appliance which is registered with the netpageNETPAGE system and prints netpageNETPAGE documents on demand and via subscription. Each printer has a unique printer ID 62, and is connected to the netpageNETPAGE network via a network such as the Internet, ideally via a broadband connection.

Apart from identity and security settings in non-volatile memory, the netpageNETPAGE printer contains no persistent storage. As far as a user is concerned, "the network is the computer". NetpagesNETPAGES function interactively across space and time with the help of the distributed netpageNETPAGE page servers 10, independently of particular netpageNETPAGE printers.

The netpageNETPAGE printer receives subscribed netpageNETPAGE documents from netpageNETPAGE publication servers 14. Each document is distributed in two parts: the page layouts, and the actual text and image objects which populate the pages. Because of personalization, page layouts are typically specific to a particular subscriber and so are pointcast to the subscriber's printer via the appropriate page server. Text and image objects, on the other hand, are typically shared with other subscribers, and so are multicast to all subscribers' printers and the appropriate page servers.

The netpageNETPAGE publication server optimizes the segmentation of document content into pointcasts and multicasts. After receiving the pointcast of a document's page layouts, the printer knows which multicasts, if any, to listen to.

Once the printer has received the complete page layouts and objects that define the document to be printed, it can print the document.

The printer rasterizes and prints odd and even pages simultaneously on both sides of the sheet. It contains duplexed print engine controllers 760 and print engines utilizing Memjet™ printheads 350 for this purpose.

The printing process consists of two decoupled stages: rasterization of page descriptions, and expansion and printing of page images. The raster image processor (RIP) consists of one or more standard DSPs 757 running in parallel. The duplexed print engine controllers consist of custom processors which expand, dither and print page images in real time, synchronized with the operation of the printheads in the print engines.

Printers not enabled for IR printing have the option to print tags using IR-absorptive black ink, although this restricts tags to otherwise empty areas of the page. Although such pages have more limited functionality than IR-printed pages, they are still classed as netpagesNETPAGES.

A normal netpageNETPAGE printer prints netpagesNETPAGES on sheets of paper. More specialised netpageNETPAGE printers may print onto more specialised surfaces, such as globes. Each printer supports at least one surface type, and supports at least one tag tiling scheme, and hence tag map, for each surface type. The

tag map 811 which describes the tag tiling scheme actually used to print a document becomes associated with that document so that the document's tags can be correctly interpreted.

Figure 2 shows the netpageNETPAGE printer class diagram, reflecting printer-related information maintained by a registration server 11 on the netpageNETPAGE network.

1.5 THE NETPAGE PEN

The active sensing device of the netpageNETPAGE system is typically a pen 101, which, using its embedded controller 134, is able to capture and decode IR position tags from a page via an image sensor. The image sensor is a solid-state device provided with an appropriate filter to permit sensing at only near-infrared wavelengths. As described in more detail below, the system is able to sense when the nib is in contact with the surface, and the pen is able to sense tags at a sufficient rate to capture human handwriting (i.e. at 200 dpi or greater and 100 Hz or faster). Information captured by the pen is encrypted and wirelessly transmitted to the printer (or base station), the printer or base station interpreting the data with respect to the (known) page structure.

The preferred embodiment of the netpageNETPAGE pen operates both as a normal marking ink pen and as a non-marking stylus. The marking aspect, however, is not necessary for using the netpageNETPAGE system as a browsing system, such as when it is used as an Internet interface. Each netpageNETPAGE pen is registered with the netpageNETPAGE system and has a unique pen ID 61. Figure 14 shows the netpageNETPAGE pen class diagram, reflecting pen-related information maintained by a registration server 11 on the netpageNETPAGE network.

When either nib is in contact with a netpageNETPAGE, the pen determines its position and orientation relative to the page. The nib is attached to a force sensor, and the force on the nib is interpreted relative to a threshold to indicate whether the pen is "up" or "down". This allows a interactive element on the page to be 'clicked' by pressing with the pen nib, in order to request, say, information from a network. Furthermore, the force is captured as a continuous value to allow, say, the full dynamics of a signature to be verified.

The pen determines the position and orientation of its nib on the netpageNETPAGE by imaging, in the infrared spectrum, an area 193 of the page in the vicinity of the nib. It decodes the nearest tag and computes the position of the nib relative to the tag from the observed perspective distortion on the imaged tag and the known geometry of the pen optics. Although the position resolution of the tag may be low, because the tag density on the page is inversely proportional to the tag size, the adjusted position resolution is quite high, exceeding the minimum resolution required for accurate handwriting recognition.

Pen actions relative to a netpageNETPAGE are captured as a series of strokes. A stroke consists of a sequence of time-stamped pen positions on the page, initiated by a pen-down event and completed by the subsequent pen-up event. A stroke is also tagged with the page ID 50 of the netpageNETPAGE whenever the page ID changes, which, under normal circumstances, is at the commencement of the stroke.

Each netpageNETPAGE pen has a current selection 826 associated with it, allowing the user to perform copy and paste operations etc. The selection is timestamped to allow the system to discard it after a defined time period. The current selection describes a region of a page instance. It consists of the most recent

digital ink stroke captured through the pen relative to the background area of the page. It is interpreted in an application-specific manner once it is submitted to an application via a selection hyperlink activation.

Each pen has a current nib 824. This is the nib last notified by the pen to the system. In the case of the default ~~netpage~~NETPAGE pen described above, either the marking black ink nib or the non-marking stylus nib is current. Each pen also has a current nib style 825. This is the nib style last associated with the pen by an application, e.g. in response to the user selecting a color from a palette. The default nib style is the nib style associated with the current nib. Strokes captured through a pen are tagged with the current nib style. When the strokes are subsequently reproduced, they are reproduced in the nib style with which they are tagged.

Whenever the pen is within range of a printer with which it can communicate, the pen slowly flashes its “online” LED. When the pen fails to decode a stroke relative to the page, it momentarily activates its “error” LED. When the pen succeeds in decoding a stroke relative to the page, it momentarily activates its “ok” LED.

A sequence of captured strokes is referred to as digital ink. Digital ink forms the basis for the digital exchange of drawings and handwriting, for online recognition of handwriting, and for online verification of signatures.

The pen is wireless and transmits digital ink to the ~~netpage~~NETPAGE printer via a short-range radio link. The transmitted digital ink is encrypted for privacy and security and packetized for efficient transmission, but is always flushed on a pen-up event to ensure timely handling in the printer.

When the pen is out-of-range of a printer it buffers digital ink in internal memory, which has a capacity of over ten minutes of continuous handwriting. When the pen is once again within range of a printer, it transfers any buffered digital ink.

A pen can be registered with any number of printers, but because all state data resides in ~~netpages~~NETPAGES both on paper and on the network, it is largely immaterial which printer a pen is communicating with at any particular time.

A preferred embodiment of the pen is described in greater detail below, with reference to Figures 6 to 8.

1.6 NETPAGE INTERACTION

The ~~netpage~~NETPAGE printer 601 receives data relating to a stroke from the pen 101 when the pen is used to interact with a ~~netpage~~NETPAGE 1. The coded data 3 of the tags 4 is read by the pen when it is used to execute a movement, such as a stroke. The data allows the identity of the particular page and associated interactive element to be determined and an indication of the relative positioning of the pen relative to the page to be obtained. The indicating data is transmitted to the printer, where it resolves, via the DNS, the page ID 50 of the stroke into the network address of the ~~netpage~~NETPAGE page server 10 which maintains the corresponding page instance 830. It then transmits the stroke to the page server. If the page was recently identified in an earlier stroke, then the printer may already have the address of the relevant page server in its cache. Each ~~netpage~~NETPAGE consists of a compact page layout maintained persistently by a ~~netpage~~NETPAGE page server (see below). The

page layout refers to objects such as images, fonts and pieces of text, typically stored elsewhere on the ~~netpage~~NETPAGE network.

When the page server receives the stroke from the pen, it retrieves the page description to which the stroke applies, and determines which element of the page description the stroke intersects. It is then able to interpret the stroke in the context of the type of the relevant element.

A “click” is a stroke where the distance and time between the pen down position and the subsequent pen up position are both less than some small maximum. An object which is activated by a click typically requires a click to be activated, and accordingly, a longer stroke is ignored. The failure of a pen action, such as a “sloppy” click, to register is indicated by the lack of response from the pen’s “ok” LED.

There are two kinds of input elements in a ~~netpage~~NETPAGE page description: hyperlinks and form fields. Input through a form field can also trigger the activation of an associated hyperlink.

2 NETPAGE PEN DESCRIPTION

2.1 PEN MECHANICS

Referring to Figures 6 and 7, the pen, generally designated by reference numeral 101, includes a housing 102 in the form of a plastics moulding having walls 103 defining an interior space 104 for mounting the pen components. The pen top 105 is in operation rotatably mounted at one end 106 of the housing 102. A semi-transparent cover 107 is secured to the opposite end 108 of the housing 102. The cover 107 is also of moulded plastics, and is formed from semi-transparent material in order to enable the user to view the status of the LED mounted within the housing 102. The cover 107 includes a main part 109 which substantially surrounds the end 108 of the housing 102 and a projecting portion 110 which projects back from the main part 109 and fits within a corresponding slot 111 formed in the walls 103 of the housing 102. A radio antenna 112 is mounted behind the projecting portion 110, within the housing 102. Screw threads 113 surrounding an aperture 113A on the cover 107 are arranged to receive a metal end piece 114, including corresponding screw threads 115. The metal end piece 114 is removable to enable ink cartridge replacement.

Also mounted within the cover 107 is a tri-color status LED 116 on a flex PCB 117. The antenna 112 is also mounted on the flex PCB 117. The status LED 116 is mounted at the top of the pen 101 for good all-around visibility.

The pen can operate both as a normal marking ink pen and as a non-marking stylus. An ink pen cartridge 118 with nib 119 and a stylus 120 with stylus nib 121 are mounted side by side within the housing 102. Either the ink cartridge nib 119 or the stylus nib 121 can be brought forward through open end 122 of the metal end piece 114, by rotation of the pen top 105. Respective slider blocks 123 and 124 are mounted to the ink cartridge 118 and stylus 120, respectively. A rotatable cam barrel 125 is secured to the pen top 105 in operation and arranged to rotate therewith. The cam barrel 125 includes a cam 126 in the form of a slot within the walls 181 of the cam barrel. Cam followers 127 and 128 projecting from slider blocks 123 and 124 fit within the cam slot 126. On rotation of the cam barrel 125, the slider blocks 123 or 124 move relative to each other to project either

the pen nib 119 or stylus nib 121 out through the hole 122 in the metal end piece 114. The pen 101 has three states of operation. By turning the top 105 through 90° steps, the three states are:

- stylus 120 nib 121 out
- ink cartridge 118 nib 119 out, and
- neither ink cartridge 118 nib 119 out nor stylus 120 nib 121 out

A second flex PCB 129, is mounted on an electronics chassis 130 which sits within the housing 102.

The second flex PCB 129 mounts an infrared LED 131 for providing infrared radiation for projection onto the surface. An image sensor 132 is provided mounted on the second flex PCB 129 for receiving reflected radiation from the surface. The second flex PCB 129 also mounts a radio frequency chip 133, which includes an RF transmitter and RF receiver, and a controller chip 134 for controlling operation of the pen 101. An optics block 135 (formed from moulded clear plastics) sits within the cover 107 and projects an infrared beam onto the surface and receives images onto the image sensor 132. Power supply wires 136 connect the components on the second flex PCB 129 to battery contacts 137 which are mounted within the cam barrel 125. A terminal 138 connects to the battery contacts 137 and the cam barrel 125. A three volt rechargeable battery 139 sits within the cam barrel 125 in contact with the battery contacts. An induction charging coil 140 is mounted about the second flex PCB 129 to enable recharging of the battery 139 via induction. The second flex PCB 129 also mounts an infrared LED 143 and infrared photodiode 144 for detecting displacement in the cam barrel 125 when either the stylus 120 or the ink cartridge 118 is used for writing, in order to enable a determination of the force being applied to the surface by the pen nib 119 or stylus nib 121. The IR photodiode 144 detects light from the IR LED 143 via reflectors (not shown) mounted on the slider blocks 123 and 124.

Rubber grip pads 141 and 142 are provided towards the end 108 of the housing 102 to assist gripping the pen 101, and top 105 also includes a clip 142 for clipping the pen 101 to a pocket.

3.2 PEN CONTROLLER

The pen 101 is arranged to determine the position of its nib (stylus nib 121 or ink cartridge nib 119) by imaging, in the infrared spectrum, an area of the surface in the vicinity of the nib. It records the location data from the nearest location tag, and is arranged to calculate the distance of the nib 121 or 119 from the location tag utilising optics 135 and controller chip 134. The controller chip 134 calculates the orientation of the pen and the nib-to-tag distance from the perspective distortion observed on the imaged tag.

Utilising the RF chip 133 and antenna 112 the pen 101 can transmit the digital ink data (which is encrypted for security and packaged for efficient transmission) to the computing system.

When the pen is in range of a receiver, the digital ink data is transmitted as it is formed. When the pen 101 moves out of range, digital ink data is buffered within the pen 101 (the pen 101 circuitry includes a buffer arranged to store digital ink data for approximately 12 minutes of the pen motion on the surface) and can be transmitted later.

The controller chip 134 is mounted on the second flex PCB 129 in the pen 101. Figure 8 is a block diagram illustrating in more detail the architecture of the controller chip 134. Figure 8 also shows representations

of the RF chip 133, the image sensor 132, the tri-color status LED 116, the IR illumination LED 131, the IR force sensor LED 143, and the force sensor photodiode 144.

5 The pen controller chip 134 includes a controlling processor 145. Bus 146 enables the exchange of data between components of the controller chip 134. Flash memory 147 and a 512 KB DRAM 148 are also included. An analog-to-digital converter 149 is arranged to convert the analog signal from the force sensor photodiode 144 to a digital signal.

An image sensor interface 152 interfaces with the image sensor 132. A transceiver controller 153 and base band circuit 154 are also included to interface with the RF chip 133 which includes an RF circuit 155 and RF resonators and inductors 156 connected to the antenna 112.

10 The controlling processor 145 captures and decodes location data from tags from the surface via the image sensor 132, monitors the force sensor photodiode 144, controls the LEDs 116, 131 and 143, and handles short-range radio communication via the radio transceiver 153. It is a medium-performance (~40MHz) general-purpose RISC processor.

15 The processor 145, digital transceiver components (transceiver controller 153 and baseband circuit 154), image sensor interface 152, flash memory 147 and 512KB DRAM 148 are integrated in a single controller ASIC. Analog RF components (RF circuit 155 and RF resonators and inductors 156) are provided in the separate RF chip.

20 The image sensor is a CCD or CMOS image sensor. Depending on tagging scheme, it has a size ranging from about 100x100 pixels to 200x200 pixels. Many miniature CMOS image sensors are commercially available, including the National Semiconductor LM9630.

The controller ASIC 134 enters a quiescent state after a period of inactivity when the pen 101 is not in contact with a surface. It incorporates a dedicated circuit 150 which monitors the force sensor photodiode 144 and wakes up the controller 134 via the power manager 151 on a pen-down event.

25 The radio transceiver communicates in the unlicensed 900MHz band normally used by cordless telephones, or alternatively in the unlicensed 2.4GHz industrial, scientific and medical (ISM) band, and uses frequency hopping and collision detection to provide interference-free communication.

In an alternative embodiment, the pen incorporates an Infrared Data Association (IrDA) interface for short-range communication with a base station or ~~netpage~~ NETPAGE printer.

30 In a further embodiment, the pen 101 includes a pair of orthogonal accelerometers mounted in the normal plane of the pen 101 axis. The accelerometers 190 are shown in Figures 7 and 8 in ghost outline.

The provision of the accelerometers enables this embodiment of the pen 101 to sense motion without reference to surface location tags, allowing the location tags to be sampled at a lower rate. Each location tag ID can then identify an object of interest rather than a position on the surface. For example, if the object is a user interface input element (e.g. a command button), then the tag ID of each location tag within the area of the input
35 element can directly identify the input element.

The acceleration measured by the accelerometers in each of the x and y directions is integrated with respect to time to produce an instantaneous velocity and position.

Since the starting position of the stroke is not known, only relative positions within a stroke are calculated. Although position integration accumulates errors in the sensed acceleration, accelerometers typically have high resolution, and the time duration of a stroke, over which errors accumulate, is short.

3 NETPAGE PRINTER DESCRIPTION

3.1 PRINTER MECHANICS

The vertically-mounted ~~netpage~~NETPAGE wallprinter 601 is shown fully assembled in Figure 9. It prints ~~netpages-~~NETPAGES on Letter/A4 sized media using duplexed 8½" Memjet™ print engines 602 and 603, as shown in Figures 10 and 10a. It uses a straight paper path with the paper 604 passing through the duplexed print engines 602 and 603 which print both sides of a sheet simultaneously, in full color and with full bleed.

An integral binding assembly 605 applies a strip of glue along one edge of each printed sheet, allowing it to adhere to the previous sheet when pressed against it. This creates a final bound document 618 which can range in thickness from one sheet to several hundred sheets.

The replaceable ink cartridge 627, shown in Figure 12 coupled with the duplexed print engines, has bladders or chambers for storing fixative, adhesive, and cyan, magenta, yellow, black and infrared inks. The cartridge also contains a micro air filter in a base molding. The micro air filter interfaces with an air pump 638 inside the printer via a hose 639. This provides filtered air to the printheads to prevent ingress of micro particles into the Memjet™ printheads 350 which might otherwise clog the printhead nozzles. By incorporating the air filter within the cartridge, the operational life of the filter is effectively linked to the life of the cartridge. The ink cartridge is a fully recyclable product with a capacity for printing and gluing 3000 pages (1500 sheets).

Referring to Figure 10, the motorized media pick-up roller assembly 626 pushes the top sheet directly from the media tray past a paper sensor on the first print engine 602 into the duplexed Memjet™ printhead assembly. The two Memjet™ print engines 602 and 603 are mounted in an opposing in-line sequential configuration along the straight paper path. The paper 604 is drawn into the first print engine 602 by integral, powered pick-up rollers 626. The position and size of the paper 604 is sensed and full bleed printing commences. Fixative is printed simultaneously to aid drying in the shortest possible time.

The paper exits the first Memjet™ print engine 602 through a set of powered exit spike wheels (aligned along the straight paper path), which act against a rubberized roller. These spike wheels contact the 'wet' printed surface and continue to feed the sheet 604 into the second Memjet™ print engine 603.

Referring to Figures 10 and 10a, the paper 604 passes from the duplexed print engines 602 and 603 into the binder assembly 605. The printed page passes between a powered spike wheel axle 670 with a fibrous support roller and another movable axle with spike wheels and a momentary action glue wheel. The movable axle/glue assembly 673 is mounted to a metal support bracket and it is transported forward to interface with the powered axle 670 via gears by action of a camshaft. A separate motor powers this camshaft.

The glue wheel assembly 673 consists of a partially hollow axle 679 with a rotating coupling for the glue supply hose 641 from the ink cartridge 627. This axle 679 connects to a glue wheel, which absorbs adhesive by capillary action through radial holes. A molded housing 682 surrounds the glue wheel, with an opening at the front. Pivoting side moldings and sprung outer doors are attached to the metal bracket and hinge out sideways when the rest of the assembly 673 is thrust forward. This action exposes the glue wheel through the front of the molded housing 682. Tension springs close the assembly and effectively cap the glue wheel during periods of inactivity.

As the sheet 604 passes into the glue wheel assembly 673, adhesive is applied to one vertical edge on the front side (apart from the first sheet of a document) as it is transported down into the binding assembly 605.

4 PRODUCT TAGGING

Automatic identification refers to the use of technologies such as bar codes, magnetic stripe cards, smartcards, and RF transponders, to (semi-)automatically identify objects to data processing systems without manual keying.

For the purposes of automatic identification, a product item is commonly identified by a 12-digit Universal Product Code (UPC), encoded machine-readably in the form of a printed bar code. The most common UPC numbering system incorporates a 5-digit manufacturer number and a 5-digit item number. Because of its limited precision, a UPC is used to identify a class of product rather than an individual product item. The Uniform Code Council and EAN International define and administer the UPC and related codes as subsets of the 14-digit Global Trade Item Number (GTIN).

Within supply chain management, there is considerable interest in expanding or replacing the UPC scheme to allow individual product items to be uniquely identified and thereby tracked. Individual item tagging can reduce “shrinkage” due to lost, stolen or spoiled goods, improve the efficiency of demand-driven manufacturing and supply, facilitate the profiling of product usage, and improve the customer experience.

There are two main contenders for individual item tagging: optical tags in the form of so-called two-dimensional bar codes, and radio frequency identification (RFID) tags. For a detailed description of RFID tags, refer to Klaus Finkenzeller, *RFID Handbook*, John Wiley & Son (1999), the contents of which are herein incorporated by cross-reference. Optical tags have the advantage of being inexpensive, but require optical line-of-sight for reading. RFID tags have the advantage of supporting omnidirectional reading, but are comparatively expensive. The presence of metal or liquid can seriously interfere with RFID tag performance, undermining the omnidirectional reading advantage. Passive (reader-powered) RFID tags are projected to be priced at 10 cents each in multi-million quantities by the end of 2003, and at 5 cents each soon thereafter, but this still falls short of the sub-one-cent industry target for low-price items such as grocery. The read-only nature of most optical tags has also been cited as a disadvantage, since status changes cannot be written to a tag as an item progresses through the supply chain. However, this disadvantage is mitigated by the fact that a read-only tag can refer to information maintained dynamically on a network.

The Massachusetts Institute of Technology (MIT) Auto-ID Center has developed a standard for a 96-bit Electronic Product Code (EPC), coupled with an Internet-based Object Name Service (ONS) and a Product Markup Language (PML). Once an EPC is scanned or otherwise obtained, it is used to look up, possibly via the ONS, matching product information portably encoded in PML. The EPC consists of an 8-bit header, a 28-bit EPC manager, a 24-bit object class, and a 36-bit serial number. For a detailed description of the EPC, refer to Brock, D.L., *The Electronic Product Code (EPC)*, MIT Auto-ID Center (January 2001), the contents of which are herein incorporated by cross-reference. The Auto-ID Center has defined a mapping of the GTIN onto the EPC to demonstrate compatibility between the EPC and current practices Brock, D.L., *Integrating the Electronic Product Code (EPC) and the Global Trade Item Number (GTIN)*, MIT Auto-ID Center (November 2001), the contents of which are herein incorporated by cross-reference. The EPC is administered by EPCglobal, an EAN-UCC joint venture.

EPCs are technology-neutral and can be encoded and carried in many forms. The Auto-ID Center strongly advocates the use of low-cost passive RFID tags to carry EPCs, and has defined a 64-bit version of the EPC to allow the cost of RFID tags to be minimized in the short term. For detailed description of low-cost RFID tag characteristics, refer to Sarma, S., *Towards the 5c Tag*, MIT Auto-ID Center (November 2001), the contents of which are herein incorporated by cross-reference. For a description of a commercially-available low-cost passive RFID tag, refer to *915 MHz RFID Tag*, Alien Technology (2002), the contents of which are herein incorporated by cross-reference. For detailed description of the 64-bit EPC, refer to Brock, D.L., *The Compact Electronic Product Code*, MIT Auto-ID Center (November 2001), the contents of which are herein incorporated by cross-reference.

EPCs are intended not just for unique item-level tagging and tracking, but also for case-level and pallet-level tagging, and for tagging of other logistic units of shipping and transportation such as containers and trucks. The distributed PML database records dynamic relationships between items and higher-level containers in the packaging, shipping and transportation hierarchy.

4.1 OMNITAGGING IN THE SUPPLY CHAIN

Using an invisible (e.g. infrared) tagging scheme to uniquely identify a product item has the significant advantage that it allows the entire surface of a product to be tagged, or a significant portion thereof, without impinging on the graphic design of the product's packaging or labelling. If the entire product surface is tagged, then the orientation of the product doesn't affect its ability to be scanned, i.e. a significant part of the line-of-sight disadvantage of a visible bar code is eliminated. Furthermore, since the tags are small and massively replicated, label damage no longer prevents scanning.

Omnitagging, then, consists of covering a large proportion of the surface of a product item with optically-readable invisible tags. Each omnitag uniquely identifies the product item on which it appears. The omnitag may directly encode the product code (e.g. EPC) of the item, or may encode a surrogate ID which in turn identifies the product code via a database lookup. Each omnitag also optionally identifies its own position on the

surface of the product item, to provide the downstream consumer benefits of ~~netpage~~NETPAGE interactivity described earlier.

Omnitags are applied during product manufacture and/or packaging using digital printers. These may be add-on infrared printers which print the omnitags after the text and graphics have been printed by other means, or integrated color and infrared printers which print the omnitags, text and graphics simultaneously. Digitally-printed text and graphics may include everything on the label or packaging, or may consist only of the variable portions, with other portions still printed by other means.

4.2 OMNITAGGING

As shown in Figure 13, a product's unique item ID 215 may be seen as a special kind of unique object ID 210. The Electronic Product Code (EPC) 220 is one emerging standard for an item ID. An item ID typically consists of a product ID 214 and a serial number 213. The product ID identifies a class of product, while the serial number identifies a particular instance of that class, i.e. an individual product item. The product ID in turn typically consists of a manufacturer number 211 and a product class number 212. The best-known product ID is the EAN.UCC Universal Product Code (UPC) 221 and its variants.

As shown in Figure 14, an omnitag 202 encodes a page ID (or region ID) 50 and a two-dimensional (2D) position 86. The region ID identifies the surface region containing the tag, and the position identifies the tag's position within the two-dimensional region. Since the surface in question is the surface of a physical product item 201, it is useful to define a one-to-one mapping between the region ID and the unique object ID 210, and more specifically the item ID 215, of the product item. Note, however, that the mapping can be many-to-one without compromising the utility of the omnitag. For example, each panel of a product item's packaging could have a different region ID 50. Conversely, the omnitag may directly encode the item ID, in which case the region ID contains the item ID, suitably prefixed to decouple item ID allocation from general ~~netpage~~NETPAGE region ID allocation. Note that the region ID uniquely distinguishes the corresponding surface region from all other surface regions identified within the global ~~netpage~~NETPAGE system.

The item ID 215 is preferably the EPC 220 proposed by the Auto-ID Center, since this provides direct compatibility between omnitags and EPC-carrying RFID tags.

In Figure 14 the position 86 is shown as optional. This is to indicate that much of the utility of the omnitag in the supply chain derives from the region ID 50, and the position may be omitted if not desired for a particular product.

For interoperability with the ~~netpage~~NETPAGE system, an omnitag 202 is a ~~netpage~~NETPAGE tag 4, i.e. it has the logical structure, physical layout and semantics of a ~~netpage~~NETPAGE tag.

When a ~~netpage~~NETPAGE sensing device such as the ~~netpage~~NETPAGE pen 101 images and decodes an omnitag, it uses the position and orientation of the tag in its field of view and combines this with the position encoded in the tag to compute its own position relative to the tag. As the sensing device is moved relative to a Hyperlabelled surface region, it is thereby able to track its own motion relative to the region and generate a set of timestamped position samples representative of its time-varying path. When the sensing device is a pen, then the

path consists of a sequence of strokes, with each stroke starting when the pen makes contact with the surface, and ending when the pen breaks contact with the surface.

When a stroke is forwarded to the page server 10 responsible for the region ID, the server retrieves a description of the region keyed by region ID, and interprets the stroke in relation to the description. For example, if the description includes a hyperlink and the stroke intersects the zone of the hyperlink, then the server may interpret the stroke as a designation of the hyperlink and activate the hyperlink.

4.3 OMNITAG PRINTING

An omnitag printer is a digital printer which prints omnitags onto the label, packaging or actual surface of a product before, during or after product manufacture and/or assembly. It is a special case of a ~~netpage~~NETPAGE printer 601. It is capable of printing a continuous pattern of omnitags onto a surface, typically using a near-infrared-absorptive ink. In high-speed environments, the printer includes hardware which accelerates tag rendering. This typically includes real-time Reed-Solomon encoding of variable tag data such as tag position, and real-time template-based rendering of the actual tag pattern at the dot resolution of the printhead.

The printer may be an add-on infrared printer which prints the omnitags after text and graphics have been printed by other means, or an integrated color and infrared printer which prints the omnitags, text and graphics simultaneously. Digitally-printed text and graphics may include everything on the label or packaging, or may consist only of the variable portions, with other portions still printed by other means. Thus an omnitag printer with an infrared and black printing capability can displace an existing digital printer used for variable data printing, such as a conventional thermal transfer or inkjet printer.

For the purposes of the following discussion, any reference to printing onto an item label is intended to include printing onto the item packaging in general, or directly onto the item surface. Furthermore, any reference to an item ID 215 is intended to include a region ID 50 (or collection of per-panel region ids), or a component thereof.

The printer is typically controlled by a host computer, which supplies the printer with fixed and/or variable text and graphics as well as item ids for inclusion in the omnitags. The host may provide real-time control over the printer, whereby it provides the printer with data in real time as printing proceeds. As an optimisation, the host may provide the printer with fixed data before printing begins, and only provide variable data in real time. The printer may also be capable of generating per-item variable data based on parameters provided by the host. For example, the host may provide the printer with a base item ID prior to printing, and the printer may simply increment the base item ID to generate successive item ids. Alternatively, memory in the ink cartridge or other storage medium inserted into the printer may provide a source of unique item ids, in which case the printer reports the assignment of items ids to the host computer for recording by the host.

Alternatively still, the printer may be capable of reading a pre-existing item ID from the label onto which the omnitags are being printed, assuming the unique ID has been applied in some form to the label during a previous manufacturing step. For example, the item ID may already be present in the form of a visible 2D bar

code, or encoded in an RFID tag. In the former case the printer can include an optical bar code scanner. In the latter case it can include an RFID reader.

The printer may also be capable of rendering the item ID in other forms. For example, it may be capable of printing the item ID in the form of a 2D bar code, or of printing the product ID component of the item ID in the form of a 1D bar code, or of writing the item ID to a writable or write-once RFID tag.

4.4 OMNITAG SCANNING

Item information typically flows to the product server in response to situated scan events, e.g. when an item is scanned into inventory on delivery; when the item is placed on a retail shelf; and when the item is scanned at point of sale. Both fixed and hand-held scanners may be used to scan omnitagged product items, using both laser-based 2D scanning and 2D image-sensor-based scanning, using similar or the same techniques as employed in the netpageNETPAGE pen.

As shown in Figure 16, both a fixed scanner 254 and a hand-held scanner 252 communicate scan data to the product server 251. The product server may in turn communicate product item event data to a peer product server (not shown), or to a product application server 250, which may implement sharing of data with related product servers. For example, stock movements within a retail store may be recorded locally on the retail store's product server, but the manufacturer's product server may be notified once a product item is sold.

4.5 OMNITAG-BASED NETPAGE INTERACTIONS

A product item whose labelling, packaging or actual surface has been omnitagged provides the same level of interactivity as any other netpageNETPAGE.

There is a strong case to be made for netpageNETPAGE-compatible product tagging. NetpageNETPAGE turns any printed surface into a finely differentiated graphical user interface akin to a Web page, and there are many applications which map nicely onto the surface of a product. These applications include obtaining product information of various kinds (nutritional information; cooking instructions; recipes; related products; use-by dates; servicing instructions; recall notices); playing games; entering competitions; managing ownership (registration; query, such as in the case of stolen goods; transfer); providing product feedback; messaging; and indirect device control. If, on the other hand, the product tagging is undifferentiated, such as in the case of an undifferentiated 2D barcode or RFID-carried item ID, then the burden of information navigation is transferred to the information delivery device, which may significantly increase the complexity of the user experience or the required sophistication of the delivery device user interface.

The invention will now be described with reference to the following examples. However, it will of course be appreciated that this invention may be embodied in many other forms without departing from the scope of the invention, as defined in the accompanying claims.

Examples

In the following examples, uv-visible spectra are reported conventionally by stating an absorption wavelength first, followed by the corresponding $\log \epsilon_{\max}$ in parentheses. For example, "760 (5.11)" denotes an absorption at 760 nm having a $\log \epsilon_{\max}$ of 5.11.

5 Example 1

Nickel dithiolene camphorsulfonic acid dipotassium salt

Phosphorous pentasulfide (12.5 g; 0.028 mol) was added to a solution of camphorquinonesulfonic acid mono-hydrate (5.1 g; 0.019 mol) in freshly distilled dioxane (150 mL). The resulting mixture was heated under reflux for 2 h under a nitrogen atmosphere. After this time the reaction mixture was cooled slightly and while still quite warm was filtered through a sintered glass funnel to remove unreacted P_4S_{10} . Nickel chloride hexahydrate (8.2 g; 0.034 mol) in water (100 mL) was added to the filtrate and the resulting mixture was heated under reflux for a further 2 h. During this time the colour changed from green/beige to black. The reaction mixture was consecutively cooled, diluted with water (200 mL), treated with tetrabutylammonium hydroxide (40%, 50 mL) and extracted with dichloromethane (3×250 mL). The dichloromethane was removed by evaporation and the residue was dissolved in ethanol (500 mL). The ethanol solution was percolated through a sintered glass funnel containing DOWEX- H^+ resin, washing with more ethanol, in order to convert the tetrabutylammonium salt into the free acid. The black ethanol solution was treated with potassium *tert*-butoxide (2 g; 0.018 mol) in ethanol (50 mL) with stirring. The resulting cloudy brown mixture was filtered, washing consecutively with ethanol, warm ethanol, warm ether, and finally warm acetone to give the nickel dithiolene dipotassium salt as a dark purple solid (3.14 g; 44%). λ_{\max} 781 (4.11), 541 (2.95); MS (ESI) m/z : 651 [(M-K) $^-$, 27%], 306 [(M-2K) $^{2-}$, 100]; HRMS: m/z calcd for $C_{20}H_{26}NiO_6S_6^{2-}$ (M $^{+}$ -2K) $^{2-}$ 305.9708, found 305.9711.

Example 2

Nickel dithiolene camphorsulfonic acid disodium salt

A mixture of camphorquinonesulfonic acid mono-hydrate (4.12 g, 0.016 mol) and phosphorous pentasulfide (10.3 g, 0.023 mol) in dioxane (100 mL) was heated at reflux for 2 h. The excess phosphorous pentasulfide was filtered off and washed with dioxane (50 mL). A solution of nickel (II) chloride hexahydrate (8.10 g, 0.034 mol) in water (50 mL) was added to the dioxane solution and the black reaction mixture heated at reflux for 2 h. The resulting dark-magenta solution was diluted with water (500 mL), filtered and extracted with chloroform (2×200 mL). The aqueous layer was basified to pH 8 with tetrabutylammonium hydroxide (40%, 60 mL) and extracted with chloroform (3×200 mL). The combined organic layers were washed with water (1×200 mL) and the solvent removed under reduced pressure. The tetrabutylammonium salt was dissolved in ethanol and eluted through a column of DOWEX- H^+ resin to give the free acid. This ethanol solution was then eluted through a column of Amberlite IRP-64 resin (Na $^+$ form) and the solvent removed to give the sodium salt as a dark-purple powder. λ_{\max} 783 nm; (ESI) m/z : 635 [(M-Na) $^-$, 27%], 306 [(M-2Na) $^{2-}$, 100]; HRMS: m/z calcd for $C_{20}H_{26}NiO_6S_6^{2-}$ (M $^{+}$ -2Na) $^{2-}$ 305.9708, found 305.9723.

Example 3*Palladium dithiolene camphorsulfonic acid dipotassium salt*

5 Phosphorous pentasulfide (1.97 g; 4.4 mmol) was added to a solution of camphorquinonesulfonic acid mono-
hydrate (0.59 g; 2.2 mmol) in freshly distilled dioxane (30 mL). The reaction mixture was heated under reflux
for 2 h and filtered. The filtrate was treated with palladium (II) acetate (0.25 g; 1.1 mmol) in water (10 mL) with
stirring causing the reaction mixture to become cloudy and then dark purple in colour. The whole was heated
under reflux for 2 h and diluted with water (300 mL). Tetrabutylammonium hydroxide solution (40%, 5 mL) was
added and then the mixture was extracted with chloroform (3 × 100 mL). The solvent was removed by
10 evaporation and the purple residue was dissolved in ethanol (50 mL) before percolating through a DOWEX-H⁺
column. The DOWEX was washed with ethanol until colourless (150 mL). The resulting ethanol solution was
treated with potassium *t*-butoxide (1 g; 8.9 mmol) and cooled causing a purple solid to separate out. The solid
was filtered, washed with ethanol (100 mL), and dried thereby affording the palladium complex as a purple solid
(0.382 g; 50%). λ_{max} 831 nm.

15